

Key **Features**

- Lifelike True Beauty: International color standard Pantone validated and 100% sRGB wide color gamut
- Precise Color: ColorPro Verified with prefactory calibration for overwhelmed Delta E <
 2 color accuracy
- Multimedia Devices: Support USB-C with 60W high-speed charging, plus HDMI 2.0, DisplayPort 1.4, USB3.2
- Unlimited Flexibility: Auto Pivot &
 Ergonomic Stand with tilt, swivel, pivot, and
 height adjustments
- The Visible Difference: 4K UHD(3840* 2160) resolution IPS panel with 32" frameless design



Product **Description**

Designed with creative professionals in mind, the ViewSonic VP3256-4K delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us www.viewsonic.com

DISPLAY		WALL MOUNT	
Display Size (in.):	32	VESA Compatible:	100 x 100 mm
Viewable Area (in.):	31.5	INPUT SIGNAL	
Panel Type:	IPS Technology	Frequency Horizontal:	15 ~ 136KHz
Resolution:	3840 x 2160	Frequency Vertical:	24 ~ 75Hz
Resolution Type:	UHD	VIDEO INPUT	
Static Contrast Ratio:	1,000:1 (typ)		TMDS - HDMI (v2.0), PCI-E -
Dynamic Contrast Ratio:	20M:1	Digital Sync:	DisplayPort (v1.4), Micro-Packet - Type C
Light Source:	LED	ERGONOMICS	<i>5.</i>
Brightness:	350 cd/m² (typ)	Height Adjust (mm):	130
Colors:	1.07B	Swivel:	120°
Color Space Support:	10 bit (8 bit + A-FRC)	Tilt (Forward/Back):	-5° / 21°
Aspect Ratio:	16:9	Pivot (Right/Left):	90° / 90°
Response Time (Typical GTG):	5ms	WEIGHT (IMPERIAL)	
, , , , ,	5ms	Net (lbs):	24
Response Time (GTG w/OD):		Net Without Stand (lbs):	15.8
Viewing Angles:	178° horizontal, 178° vertical	Gross (lbs):	33.7
Backlight Life (Hours):	30000 Hrs (Min)	WEIGHT (METRIC)	
Curvature:	Flat	Net (kg):	10.9
Refresh Rate (Hz):	60	Net Without Stand (kg):	7.2
Adaptive Sync:	Yes	Gross (kg):	15.3
Blue Light Filter:	Yes	DIMENSIONS (IMPERIAL) (W	
Flicker-Free:	Yes	Packaging (in.):	33.1 x 20.5 x 12.8
Color Gamut:	Adobe RGB: 95% size / 82% coverage (Typ)DCI-P3: 95% size / 90% coverage (Typ)EBU: 127% size / 100% coverage (Typ)REC709: 128% size / 100% coverage (Typ)SMPTE-C: 139% size / 100% coverage (Typ)NTSC: 91% size (Typ)sRGB:	Physical (in.):	28.2 x 20.23~25.35 x 10.4
		Physical Without Stand (in.):	28.2 x 16.7 x 2.6
		DIMENSIONS (METRIC) (WXHXD)	
		Packaging (mm):	840 x 520 x 326
D: 10:	128% size / 100% coverage (Typ)	Physical (mm):	715 x 513.8~643.8 x 265
Pixel Size:	0.182 mm (H) x 0.182 mm (V)	Physical Without Stand (mm):	715 x 423 x 66
Surface Treatment:	Anti-Glare, Hard Coating (3H)	GENERAL	
COMPATIBILITY DO Description (many)	20.4024.00		cTUVus, FCC-B, ICES003, Energy
PC Resolution (max):	3840x2160	Regulations:	Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, CCC, China ROHS, China Energy Label
Mac® Resolution (max): PC Operating System:	3840x2160 Windows 7/8/8.1/10 certified; macOS tested		
Mac® Resolution (min):	3840x2160		VP3256-4K x1, 3-pin Plug (IEC C13 /
CONNECTOR	004002100	PACKAGE CONTENTS:	CEE22) x1, HDMI Cable (v2.0; Male- Male) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable
USB 3.2 Type A Down Stream:	2		
USB 3.2 Type B Up Stream:	1		(v3.2; Male-Male) x1, Quick Start Guide x1
USB 3.2 Type C Up Stream;			Please dispose of in accordance with
DisplayPort Alt mode : HDMI 2.0 (with HDCP 2.2):	2	Recycle/Disposal:	local, state or federal laws. *Warranty offered may differ from
DisplayPort:	1	Warranty:	market to market
Power in:	3-pin Socket (IEC C14 / CEE22)	Power Management:	Energy Star standards, EPEAT
AUDIO	- J 200.00 (IEO 017/ OEL22)		
Internal Speakers:	3Watts x2		
POWER			
Eco Mode (Conserve):	32W		
Eco Mode (optimized):	39W		
Consumption (typical):	46W		
Consumption (max):	50W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS	=		
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		

Humidity (non-condensing):

20% to 90%