

# UK CE

#### Disposal and recycling information


The crossed-out wheeled bin symbol means that this product must be disposed separately from household waste. As an end user, you are obliged to dispose the product in accordance with the respective national regulations for separate collection, for example by depositing it at an official collection point. Returning it to the retailer is also possible if the distributor offers voluntary return or is legally obliged to do so.

Separate collection is a valuable contribution to the protection of the environment and human health, as the proper treatment of waste equipment avoids potential negative effects caused by the presence of hazardous substances and protects raw materials by recovering them.

In addition, please note that waste prevention makes an even more valuable contribution to environmental protection. Where possible, therefore, in addition to continued own use or repair, handing over to secondary users is an ecologically valuable alternative to disposal.

Bechtle Logistik & Service GmbH Bechtle Platz 1 74172 Neckarsulm Germany 4734416

# Adapter USB Type-C/male - HDMI/female



Please read these instructions carefully before using the product and store them properly.



#### Introduction

Thanks for choosing the ARTICONA USB 3.2 Type C to HDMI adapter, designed for connecting High definition TVs and monitors to a USB Type C computer. The adapter can be connected to an HDMI cable, which can then be connected to the display.

Note: The computers USB type C port needs to support video and data transmission to work.

#### **Features**

- · USB-C/DisplayPort HBR3 Alt-mode input port
- · Transfer of audio and video signal
- · Data transfer rate: 48 Gbit/s
- · 7680×4320@60Hz, 3840×2160@120Hz
- · No driver needed
- Aluminium Housing
- Integrated 15cm cable
- Plug and play, hot swap
- Supports 3D/HDCP2.3/HDR10+/DSC/VRR/QMS/QFT/ ALLM/CEC
- · Easy to carry and use

## **Specifications**

Input port USB 3.2 Type C male

Output port HDMI A female

Max. supported 7680×4320@60Hz, resolution 3840×2160@120Hz

Operating Temperature 0°C ~ 45°C

Operating Humidity 10% ~ 85% RH

(no condensation) Storage Temperature  $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ 

storage remperature 20 0 70 0

(no condensation)

Compatible operating

Storage Humidity

systems

Housing material Aluminium

### Operation

 Connect one end of an HDMI cable to the adapter and the other end to your TV or monitor.

10% ~ 85% RH

Windows, macOS, Chrome OS

2. Connect the Type C plug of the adapter to your computer.