

Product datasheet

Specifications



EasyPDU, Switched, Zero U, 22 kW, 230V, (18) C13 & (6) C19 ; IEC309



EPDU1232S

Overview

Lead time

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 3P + N + PE

Physical

Colour	Black
Height	1794 mm
Width	55 mm
Depth	62 mm
Net weight	8.17 kg
Mounting location	Side
Mounting position	Vertical

Input

Input current limits	32 A
Load capacity	22 kW
Network frequency	50/60 Hz
Plug standard	IEC 60309

Output

Number of power socket outlets	18 IEC 60320 C13 6 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product certifications	CE EAC RCM TÜV
------------------------	-------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %

Packing Units

Number of Units in Package 1	1
Package 1 Height	1950 mm
Package 1 Width	160 mm
Package 1 Length	110 mm
Package 1 Weight	9.45 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Recommended replacement(s)