Product datasheet

Specifications





APC NetShelter SX, Server Rack Enclosure, 42U, Shock Packaging, 2000 lbs, Black, 1991H x 750W x 1200D mm

AR3350SP

Q .		
Overview Presentation	NetShelter SX cabinet and packaging system designed to safely integrate, transport, unload and deploy up to 2000 lbs (907 kg) of IT equipment. The cabinet is paired with a shock absorbing pallet, unloading ramp, and impact resistant shell. The system has been engineered, tested and approved for secure shipment of fully converged systems such as being certified with Cisco® for pre-racking and shipping Cisco Unified Computing System (UCS).	
Lead time		
Main		
Number of rack unit	42U	
Provided equipment	Baying hardware Documentation CD Key(s) Leveling feet Mounting hardware Pre-installed casters Side panels User manual	
Physical		
Colour	Black	
Height	199.1 cm	
Width	75 cm	
Depth	120 cm	
Net weight	161.36 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	
Maximum mounting depth	104.8 cm	
Minimum mounting depth	26.19 cm	
Rack width	19"	
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 16 gauge rear door 18 gauge roof 18 gauge side panels	
Permanent permissible load	1020.58 kg dynamic 1700.97 kg static	



Conformance

Standards	UL 2416 UL 60950-1 EIA-310E	
Packing Units		

Package 1 Weight	275.33 kg
Package 1 Height	217.9 cm
Package 1 width	110.5 cm
Package 1 Length	132.1 cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
Take-back	Take-back program available	

Contractual warranty

Warranty	5 year repair or replace