

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Workstation CELSIUS W570

### Mini CAD Powerhouse

If you thought you would need to sacrifice performance, expandability, price or energy efficiency in a microtower design – think again. As an industry first, the FUJITSU CELSIUS W570 desktop workstation goes far and beyond with its innovative 21 liter, space-saving microtower design. No compromise for architects, designers and engineers.

#### No compromise in terms of performance, expandability and price

Designed with CAD customers in mind: performance, reliability and great flexibility - at an affordable price

- Choose between the energy-efficient Intel® Core™ processors or the powerful Intel® Xeon® E3-1200 v6 processor family
- Support of Windows 10 Pro
- Support of Windows 7 with selected processors
- 64 GB DDR4 2,400 MHz memory (incl. ECC)
- Maximum capacity of 16 TB
- Boost your storage performance with super-fast PCIe SSDs

#### Innovative, new space saving design

Our lightest and most energy efficient microtower desktop workstation

- Industry first: 21 liter desktop workstation
- Up to NVIDIA® Quadro® P2000 - optimized for CAD and AEC applications
- Optimized thermal management and cooling solutions
- Enjoy a silent workplace environment thanks to a low noise emission of only 18 dB(A)
- 280W only power supply for reduced energy consumption
- Designed, engineered and produced in Germany

#### Multi-monitor experience

Ideal for control rooms, surveillance or financial services companies

- Up to 8 monitors with the NVIDIA® Mosaic™ technology

#### 2-in-1: Workstation & Point-of-Sales device

Your workstation can not only be deployed as a traditional workstation but also as a point-of-sales device in any retail environment

- Connect your cash drawer and your scanner to two serial ports
- Support of 24/7 operation with reliable high-endurance and business critical drives



# Components

<b>Processor</b>	Intel® Xeon® processor E3-1285v6 (4 Cores / 8 Threads, 4.10 GHz, up to 4.5 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1280v6 (4 Cores / 8 Threads, 3.90 GHz, up to 4.2 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1280v5 (4 Cores / 8 Threads, 3.70 GHz, up to 4.0 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1275v6 (4 Cores / 8 Threads, 3.80 GHz, up to 4.2 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1275v5 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics P530) *	
	Intel® Xeon® processor E3-1270v6 (4 Cores / 8 Threads, 3.80 GHz, up to 4.2 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1270v5 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1245v6 (4 Cores / 8 Threads, 3.70 GHz, up to 4.1 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1245v5 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics P530) *	
	Intel® Xeon® processor E3-1240v6 (4 Cores / 8 Threads, 3.70 GHz, up to 4.1 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1240v5 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1230v6 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1230v5 (4 Cores / 8 Threads, 3.40 GHz, up to 3.8 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1225v6 (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1225v5 (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 8 MB, Intel® HD Graphics P530) *	
	Intel® Xeon® processor E3-1220v6 (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 8 MB) *	
	Intel® Xeon® processor E3-1220v5 (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 8 MB) *	
	Intel® Core™ i7-7700 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.2 GHz, 8 MB, Intel® HD Graphics 630) *	
	Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, **	
	Intel® Core™ i5-7600 processor (4 Cores / 4 Threads, 3.50 GHz, up to 4.1 GHz, 6 MB, Intel® HD Graphics 630) *	
	Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) *	
	Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, **	
	Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, **	
	Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630)	
	Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) **	
	Intel® vPro™ with all Intel® Xeon® processors No Intel® vPro™ technology with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) **6th generation Intel® processor	
<b>Operating systems</b>		
<b>Operating system pre-installed</b>	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional (available through downgrade rights from Windows 10 Pro)	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional (available through downgrade rights from Windows 10 Pro)
<b>Operating system compatible</b>	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Linux	Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) Linux
<b>Microsoft OS support information</b>	Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see Microsoft Support Lifecycle. Downgrade to Microsoft Windows 7 Professional only available with 6th generation Intel® processor	Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see Microsoft Support Lifecycle. Downgrade to Microsoft Windows 7 Professional only available with 6th generation Intel® processor
<b>Operating system notes</b>	Certified for Red Hat® Enterprise Linux (pending) Certified for SUSE Enterprise Desktop (pending) Certified for SUSE Enterprise Server (pending) For some configurations third party drivers are currently not available or configuration restrictions may apply.	Certified for Red Hat® Enterprise Linux (pending) Certified for SUSE Enterprise Desktop (pending) Certified for SUSE Enterprise Server (pending) For some configurations third party drivers are currently not available or configuration restrictions may apply.

**Memory modules**

4 GB (1 module(s) 4 GB) DDR4, unbuffered, ECC, 2,400 MHz, UDIMM  
 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM  
 8 GB (1 module(s) 8 GB) DDR4, unbuffered, ECC, 2,400 MHz, UDIMM  
 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM  
 16 GB (1 module(s) 16 GB) DDR4, unbuffered, ECC, 2,400 MHz, UDIMM  
 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM

**Graphics**

High-end 3D: NVIDIA® Quadro® P4000, 8 GB, PCIe x16, 4 x DisplayPort  
 Midrange 3D: NVIDIA® Quadro® P2000, 5 GB, PCIe x16, 4 x DisplayPort  
 Midrange 3D: AMD Radeon Pro™ WX5100, 8 GB, 320 stream processors, PCIe x16, 4 x DisplayPort  
 Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4x miniDP  
 Entry 3D: AMD Radeon Pro™ WX3100, 4 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP  
 Entry 3D: NVIDIA® Quadro® P600, 2 GB, PCIe x16, 4x miniDP  
 Entry 3D: AMD Radeon Pro™ WX2100, 2 GB, 320 stream processors, PCIe x16, 1x DisplayPort, 2x miniDP  
 Entry 3D: AMD FirePro™ W2100, 2 GB, 320 stream processors, PCIe x16, 2x DisplayPort  
 Entry 3D: NVIDIA® Quadro® P400, 2 GB, PCIe x16, 3x miniDP  
 Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP  
 Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP  
 Others: VGA Extension Card

**Notes**

NVIDIA® Quadro® P4000 requires CELSIUS W570power or CELSIUSpower+.

<b>Hard disk drives (internal)</b>	SSD PCIe, 1024 GB M.2 NVMe Highend module
	SSD PCIe, 512 GB M.2 NVMe Highend module
	SSD PCIe, 256 GB M.2 NVMe Highend module
	SSD PCIe, 1x1024 GB M.2 NVMe Highend card
	SSD PCIe, 1x 512 GB M.2 NVMe Highend card
	SSD PCIe, 1x 256 GB M.2 NVMe Highend card
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
	SSD PCIe, 1x 1024 GB M.2 NVMe card
	SSD PCIe, 1x 512 GB M.2 NVMe card
	SSD PCIe, 1x 256 GB M.2 NVMe card
	SSD SATA III, 960 GB High Endurance, 2.5-inch
	SSD SATA III, 480 GB High Endurance, 2.5-inch
	SSD SATA III, 240 GB High Endurance, 2.5-inch
	SSD SATA III, 1024 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	SSD SATA III, 512 GB, 2.5-inch, SED
	SSD SATA III, 256 GB, 2.5-inch, SED
	HDD SATA III, 7,200 rpm, 6,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch
	HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch
	16 GB, M.2 module, Flash drive
<b>Hard disk notes</b>	<p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p> <p>24/7 ready (business critical HDDs required)</p> <p>Up to 20 GB of HDD space is reserved for system recovery</p> <p>SSHD (Solid State Hard Disk, Hybrid drive)</p> <p>SED (Self-Encrypting Drive)</p> <p>SSD (Solid State Disk)</p>
<b>Drives (optional)</b>	BD Triple Writer SATA ultra slim (tray)
	DVD-ROM
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 24in1 USB 2.0 3.5"
<b>Interface add on cards/components (optional)</b>	WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)
	WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)
	Parallel Interface
	Gigabit Ethernet PCIe x1, DS
	eSATA Interface
	Dual serial card PCIe x1

Base unit	CELSIUS W570	CELSIUS W570power
<b>Mainboard</b>		
Mainboard type	D3517	
Chipset	Intel® C236	
Processor socket	LGA 1151	
Processor quantity maximum	1	
Supported capacity RAM (max.)	64 GB	
Memory slots	4 DIMM (DDR4) ECC/non-ECC	
Memory frequency	2,400 MHz	
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. DDR4 2,400 MHz will be clocked with 2,133 MHz in combination with 6th generation Intel® processor	
LAN	10/100/1,000 MBit/s Intel® I219LM	
BIOS version	AMI Aptio V	
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)	
Audio type	On board	
Audio codec	Realtek ALC671	
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound	
<b>I/O controller on board</b>		
Serial ATA total	8	
thereof SATA III	8	
thereof eSATA	2 (optional)	
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10	
<b>Interfaces</b>		
Audio: line-in	1	
Audio: line-out	1	
Front audio: microphone	1	
Front audio: headphone	1	
Internal speakers	1	
USB 2.0 total	6	
USB 3.1 Gen1 (USB 3.0) total	7	
USB 3.1 Gen2 total	optional via add on card	
USB front	2x USB 2.0; 2x USB 3.0; 1x USB 3.1 Type C (Gen1); optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay	
USB rear	2x USB 2.0; 4x USB 3.0	
USB internal	2x USB 2.0 + 1x USB A 2.0	
VGA	optional: via adapter card	
DisplayPort	2	
DVI	1 (DVI-D)	
Serial (RS-232)	optional: first and 2nd serial port (9pin, 16 byte FIFO, 16550 compatible)	
Mouse / Keyboard (PS/2)	2	
Ethernet (RJ-45)	1	
Parallel	1 (optional) (25pin with EPP and ECP)	
eSATA	1 (optional)	
Interface Module notes	Anytime USB charge functionality, USB Typ C connector supports up to 15W	

**Input device / components**

<b>Input devices (optional)</b>	Keyboard Mouse KBPC PX ECO Mouse M440 ECO Space Explorer USB
<b>Drive bays total</b>	6
<b>2.5-inch internal bays</b>	1
<b>3.5-inch internal bays</b>	2
<b>3.5-inch external bays</b>	1
<b>5.25-inch external bays</b>	2
<b>Drive bay notes</b>	5,25" bays: one bay in HH format, one bay for slim optical disc drive only; internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws);
<b>M.2-2280</b>	1 x on mainboard (for PCIe or SATA SSD modules), supports Intel® Optane™ technology

**Slots**

<b>PCI-Express 3.0 x1</b>	2 x (215 mm / 170 mm / ) Full height
<b>PCI-Express 3.0 x4 (mech. x16)</b>	1 x (215 mm / ) Full height
<b>PCI-Express 3.0 x16</b>	1 x (240 mm / ) Full height

<b>Graphics brand name</b>	Intel® HD Graphics P630, Intel® HD Graphics 630, Intel® HD Graphics P530, Intel® HD Graphics 530
<b>Shared video memory</b>	up to 1,782 MB

<b>TFT resolution (VGA)</b>	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
-----------------------------	--

<b>TFT resolution (DVI)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
-----------------------------	---

<b>TFT resolution (DisplayPort)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
-------------------------------------	---

<b>Graphics features</b>	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
--------------------------	---

<b>Graphics notes</b>	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz	
<b>Electrical values</b>		
<b>Rated voltage range</b>	100 V - 240 V	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	280 W	400 W
<b>Dimensions / Weight / Environmental</b>		
<b>Dimensions (W x D x H)</b>	180 x 304 x 375 mm 7.09 x 11.97 x 14.76 inch	
<b>Operating position</b>	Vertical	
<b>Weight</b>	approx. 10 kg	approx. 12 kg
<b>Weight (lbs)</b>	approx. 30.86 lbs	
<b>Weight notes</b>	Actual weight may vary depending on configuration	
<b>Operating ambient temperature</b>	10 - 35 °C (50 - 95 °F)	
<b>Operating relative humidity</b>	5 - 85 % (relative humidity)	
<b>Compliance</b>		
<b>Product</b>	CELSIUS W570	CELSIUS W570power
<b>Model</b>	MI6W	
<b>Germany</b>	TÜV GS	
<b>Europe</b>	CE	
<b>USA/Canada</b>	FCC Class B cCSAus	
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 in progress EPEAT® in progress (dedicated regions)	
<b>China</b>	CCC TPM 2.0 for China (optional)	
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	
<b>Additional Software</b>		
<b>Additional software (preinstalled)</b>	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office)	
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL	
<b>Security</b>		
<b>Physical Security</b>	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
<b>System and BIOS Security</b>	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces

<b>Security</b>		
<b>User Security</b>	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
<b>Workplace Embedded Tools</b>	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)
<b>Manageability</b>		
<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 11.6 (depending on processor)	
<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management	
<b>DeskView components</b>	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)	
<b>Supported standards</b>	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
<b>Manageability link</b>	<a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>	
<b>Miscellaneous</b>		
	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime 24/7 (limited configurations)	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime 24/7 (limited configurations)
<b>Warranty</b>		
<b>Warranty period</b>	3 years (depending on country)	
<b>Warranty type</b>	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)	
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>	
<b>Product Related Services - the perfect extension</b>		
<b>Recommended Service</b>	X - 9x5, Onsite Response Time: Next Business Day	
<b>Spare Parts availability</b>	5 years after end of product life	
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>	

## Recommended Accessories

---

**SpaceMouse™ Pro**



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:  
S26381-K459-L100

---

**UC&C USB Value Headset**



The FUJITSU UC&C USB Value Headset is a lightweight bi-aural full-size stereo headset with high wearing comfort. This Lync-tested USB-Headset has an appropriate Inline-Controller which supports easy call management. A noise cancelling microphone facilitates undisturbing clear phone calls.

Order Code:  
S26391-F7139-L20

---

**Keyboard KBPC PX ECO**



Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1\*\* (\*\*:  
country specific variation)

# More information

## Fujitsu OPTIMIZATION Services

In addition to the FUJITSU Workstation CELSIUS W570, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about the FUJITSU Workstation CELSIUS W570, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. [www.fujitsu.com/fts/CELSIUS](http://www.fujitsu.com/fts/CELSIUS)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2017 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2017-11-08 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2017 Fujitsu Technology Solutions GmbH