

USB 3.0 to VGA Adapter - 1920x1200

Product ID: USB32VGAPRO



The USB32VGAPRO USB 3.0 to VGA Adapter turns an available USB 3.0 port on your desktop or laptop into a VGA output, with high resolution 1920x1200/1080p video support - a convenient external video solution that makes it easy to add multi-monitor capability to a USB 3.0-enabled Mac or PC (optimal performance from USB 3.0, backward compatible with USB 2.0).

Leveraging the high-bandwidth (5 Gbps) SuperSpeed USB 3.0 interface, and powered by the DisplayLink chipset, the USB32VGAPRO is our highest performing USB to VGA adapter, delivering high-resolution content to your VGA-capable display. The external graphics card can be used to mirror your primary desktop, showing the same image on each display, or to extend your desktop to double your workspace and increase your productivity.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

USB 3.0 port (backward compatible with USB 2.0)

Certifications, Reports and Compatibility

Applications

- Add a secondary VGA display and extend your desktop without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to create engaging multimedia presentations

- Use the adapter to connect your PC to your VGA-equipped TV, for showing family pictures and movies
- Great for researchers and writers, offering the ability to have reference material on one display and a working document copy on the other
- Increase productivity by running multiple applications on different screens, check your e-mail on one display and search the web on the other
- View a large spreadsheet or several individual spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using laptop PCs, enabling connection to a secondary display/projector

Features

- SuperSpeed USB 3.0 (5 Gbps)
- Supports video resolutions up to 1920x1200/1080p
- USB-powered - No external power adapter required
- Supports Mirrored, Extended or Primary display configurations
- Supports display rotation
- NOTE: This adapter will not work with macOS (v 10.13.4-6). We recommend users update to 10.14 or later to ensure compatibility with DisplayLink

Hardware

Warranty	2 Years
AV Input	USB 3.0
AV Output	VGA
USB Pass-Through	No
Memory	512MB
Chipset ID	DisplayLink - DL-3100N

Performance

Maximum Analog Resolutions	1920x1200/1080p
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1366x768, 1280x800, 1280x768, 1280x720



Standard(16/32 bit):

1600x1200, 1400x1050, 1280x1024, 1024x768, 800x600,
640x480

Wide Screen Supported Yes

General Specifications Note: If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.

This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.

Connector(s)

Connector A	USB Type-A (9 pin) USB 3.0 (5 Gbps)
Connector B	VGA (15 pin, High Density D-Sub)

Software

OS Compatibility	Windows XP (32-bit), Vista, 7, 8, 8.1, 10, 11 macOS 10.6 - 10.12, 10.14 - 10.15, 11.0, 12.0 Ubuntu 18.04, 20.04 Chrome OS v55+
------------------	---

Special Notes / Requirements

System and Cable Requirements	System Processor: Quad Core 2.4GHz (i5 recommended) System Memory: 4GB
-------------------------------	---

Note	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as Trigger or Fresco Logic
------	--

Connect a maximum of five USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources

This USB video adapter is not intended for graphical intensive applications, such as gaming

Power



Power Source USB-Powered

Environmental

Operating Temperature 10C to 40C (50F to 104F)

Storage Temperature -10C to 80C (14F to 167F)

Humidity <85% RH Non-Condensing

Physical Characteristics

Color Black

Material Plastic

Cable Length 6.2 in [15.9 cm]

Product Length 10.0 in [25.5 cm]

Product Width 2.2 in [55 mm]

Product Height 0.8 in [20 mm]

Weight of Product 2.3 oz [64 g]

Packaging Information

Package Length 8.3 in [21.2 cm]

Package Width 5.7 in [14.6 cm]

Package Height 1.6 in [40 mm]

Shipping (Package) Weight 5.6 oz [158 g]

What's in the Box

Included in Package USB 3.0 to VGA Video Adapter

 Driver/Software CD

 Instruction Manual

**Product appearance and specifications are subject to change without notice.*

