

# Product datasheet

Specifications



## Rack PDU, Switched, 2U, 32A, 230V, (16)C13

AP7922B

### Overview

Lead time

### Main

<b>Main Input Voltage</b>	200 V 208 V 230 V
<b>Main Output Voltage</b>	230 V
<b>Input Connection Type</b>	IEC 60309 32 A 2P + E
<b>Number of rack unit</b>	2U
<b>Cable length</b>	3.05 m
<b>Number of cables</b>	1
<b>Provided equipment</b>	Documentation CD Installation guide Rack mounting brackets

### Physical

<b>Colour</b>	Black
<b>Height</b>	8.9 cm
<b>Width</b>	44.5 cm
<b>Depth</b>	11.4 cm
<b>Net weight</b>	4.5 kg
<b>Mounting location</b>	Front Rear
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted

### Input

<b>Permissible voltage</b>	220...240 V
<b>Input current limits</b>	32 A
<b>Load capacity</b>	7360 VA
<b>Network frequency</b>	50/60 Hz

## Output

Number of power socket outlets 16 IEC 60320 C13

## Conformance

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

## Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	6.55 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty 2 years repair or replace

## Recommended replacement(s)