



# APC Smart-UPS Ultra On-Line Lithium ion, 8KVA/8KW, 4U Rack/ Tower, 230V

SRTL8KRM4UI

			W

Lead time

#### Main

Main Input Voltage	220240 V
Other Input Voltage	220240 V
Rated power in W	8000 W
Rated power in VA	8000 VA
Number of rack unit	1U
Number of cables	1
Battery type	Li-lon (Lithium-lon)
Provided equipment	RJ45 cable

#### **Batteries & Runtime**

Battery recharge time	1.5 h
Battery voltage	180 V
Battery charger power	1200 W rated

#### General

Redundant No.

## **Physical**

Colour	Silver grey	
Height	432 mm	
Width	731 mm	
Depth	175 mm	
Mounting mode	Rack-mounted with kit	
USB compatible	No	

#### Input

Network frequency 50/60 Hz

## Output

Maximum configurable power in W	8000 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Double conversion online
Wave type	Sine wave
Maximum configurable power in VA	8000 VA

#### Conformance

Standards UL 1778

#### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	0.0015240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

## **Communications & Management**

Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49.6 cm
Package 1 Width	62.5 cm
Package 1 Length	95.8 cm
Package 1 Weight	60 kg
SCC14	1073130457849

# Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
RoHS exemption information	Yes	

## **Contractual warranty**

Warranty

5 years repair or replace

Recommended replacement(s)