

BOSTON BUSINESSLINE SERVER SERIES

FENWAY-22X224N.4



PART NO: P3815



TECHNICAL SPECIFICATIONS

CHIPSET	Intel® SoC
SOCKET	Dual Socket E2 (LGA-4710) supports Intel® Xeon® 6500 & 6700 Processors
MEMORY	max. 8.0TB DDR5-6400 ECC registered
LAN	Dual Port 10GBase-T Grand Twin Network Adapter, based on Broadcom BCM57416, 2x RJ45
GRAPHIC / AUDIO / GPU	DC-SCM module with OpenBMC
SAS / SATA / NVMe	12x NVMe PCI-E 5.0 x4 2x M.2 Port, PCI-E 5.0 x4, M-Key, Form Factor 2280, 22110
NO MAX. HDD/SSD	24x 2.5" Hot-swap NVMe drive bays
EXPANSION SLOTS	2x PCI-E 5.0 x16 2x AIOM/OCF 3.0 PCI-E 5.0 x16 network slots
USB	2x USB 3.0 (2x rear)
INPUT / OUTPUT	-
REMOTE / IPMI	IPMI 2.0, remote KVM console w/ virtual media, power control, health values, dedicated LAN
TPM	1x TPM 2.0 header
POWER SUPPLY	Redundant 2000W AC w/ PFC, 80 PLUS Titanium Level Certified

CONFIGURATION

(individual adaptations possible)

CHASSIS
2U Rackmount Server

DIMENSIONS (HxWxD)
88x438x780mm

POWER SUPPLY
Redundant 2000W AC w/ PFC, 80 PLUS Titanium Level Certified

MOTHERBOARD
Dual Socket E2 (LGA-4710)
supports Intel® Xeon® 6500 & 6700 Processors

CPU
2x Intel® Xeon® 6505P, 12-Cores,
2.20 GHz, HT, 48MB L3-Cache,
LGA-4710 E2B 2S, 150W (Granite Rapids SP)

MEMORY
16x 32GB (total 512GB) DDR5-6400, ECC registered

HARDWARE RAID
Optional

STORAGE DRIVES
960GB TLC, NVMe PCI-E 4.0 x4,
2.5" U.2, 1 DWPD (read intensive)

OPERATIONAL SYSTEM
Optional:
Microsoft® Windows™ Server
Red Hat Enterprise Standard Linux

SUPPORT SERVICES
36 month (Bring In)
Optional:
36 month onsite 9/5 NBD

DEUTSCHLAND

BOSTON Server & Storage Solutions GmbH
Kapellenstrasse 11 • 85622 Feldkirchen
T. +49 89 90901993 • sales@boston-it.de
www.boston-it.com/de

ÖSTERREICH

BOSTON Server & Storage Solutions GmbH
T. +43 660 2090400
E. sales@boston-it.at
www.boston-it.com/at

SCHWEIZ

BOSTON Server & Storage Solutions GmbH
Hafenstrasse 50C • 8280 Kreuzlingen
T. +41 71 5542275 • sales@boston-it.ch
www.boston-it.com/ch