

DATASHEET

Power Cable CEE7/7 180° - C13 180°, Grey, 2.0 m, 3 x 0.75 mm²



General data

10 A / 250 V VDE tested
Suitable for Germany, Belgium, France and further

Allgemeine Daten

Number of cores	3
Spiralized cable	True
With cord switch	True
Colour outer sheath	grey
Material outer sheath	Polyvinyl chloride (PVC)
Halogen free	False

Mechanische Eigenschaften

Connection 1	Socket outlet with protective contact, straight
Connection 2	Cold device plug straight, female

Kabelmantel

Temperature resistance	0 - 70 °C
Oil resistant (according to EN 60811-404)	False

Elektrische Eigenschaften

Protective conductor	True
Nominal voltage	250 V

This datasheet was created automatically on 11-05-2023 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 180° - C13 180°, Grey, 2.0 m, 3 x 0.75 mm²

Normen, Zulassungen, Zertifizierungen

Oil resistant (acc. EN 60811-2-1) True

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	With protective conductor	Leiternennquerschnitt	Außendurchmesser ca.
EK508.2	Power Cable CEE7/7 180° - C13 180°, Grey, 2.0 m, 3 x 0.75 mm ²	grey	2.0 m	True	0,75 mm ²	6,8 mm
EK508.3	Power Cable CEE7/7 180° - C13 180°, Grey, 3.0 m, 3 x 1.00 mm ²	grey	3.0 m	True	1,00 mm ²	7,1 mm
EK508.5	Power Cable CEE7/7 180° - C13 180°, Grey, 5.0 m, 3 x 1.00 mm ²	grey	5.0 m	True	1,00 mm ²	7,1 mm

This datasheet was created automatically on 11-05-2023 . Technical changes reserved.

