

# AXIS TM1901 Wireless Kit

## Kit for AXIS M1075-L Box Camera

The kit includes a wireless adapter and a power injector for AXIS M1075-L Box Camera. This allows the camera to connect to both 2.4 GHz and 5 GHz wireless networks. The wireless adapter supports 802.11ac/b/g/n/a. The power injector is powered by 100-240 V AC (50-60 Hz).

- > [Wireless communication](#)
- > [Plug-and-play](#)
- > [2.4 GHz and 5 GHz](#)
- > [Supports 802.11ac/b/g/n/a](#)



## AXIS TM1901 Wireless Kit

<b>Network</b>		<b>Weight</b>	Wireless adapter: 3.3 g ±0.25 g (0.007 lb±0.0006 lb) Power injector: 100 g (0.2 lb)
<b>Wireless interface</b>	Supports 802.11ac/b/g/n/a Frequency 2.4 GHz and 5 GHz	<b>Box content</b>	Wireless adapter, power injector, power cable, installation guide
<b>Approvals</b>		<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
<b>EMC</b>	Power injector: EN 55035, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, RCM AS/NZS CISPR 32 Class A, ICES-3(A)/NMB-3(A), VCCI Class A, KS C 9547, FCC Part 15 Subpart B Class A	<b>Export control</b>	This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.
<b>Safety</b>	IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1	<b>Sustainability</b>	
<b>Wireless</b>	EN 300328, EN 300440, EN 301489-1, EN 301489-3, EN 301489-17, EN 301893, EN 50566, EN 62479, EN 62209-2	<b>Substance control</b>	PVC free, BFR/CFR free in accordance with JEDEC/ECA Standard JS709 RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see <a href="https://axis.com/partner">axis.com/partner</a> .
<b>General</b>		<b>Materials</b>	To read more about sustainability at Axis, go to <a href="https://axis.com/about-axis/sustainability">axis.com/about-axis/sustainability</a>
<b>Power</b>	100–240 V AC (50–60 Hz), 0.8 A	<b>Environmental responsibility</b>	<a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> Axis Communications is a signatory of the UN Global Compact, read more at <a href="https://unglobalcompact.org">unglobalcompact.org</a>
<b>Operating conditions</b>	0 °C to 35 °C (32 °F to 95 °F)		
<b>Storage conditions</b>	-20 °C to 75 °C (-4 °F to 167 °F)		
<b>Dimensions</b>	Wireless adapter: 29.5 x 15 x 8 mm (1.2 x 0.6 x 0.3 in) Power injector: 106 x 40 x 27 mm (4.2 x 1.6 x 1.1 in) Cable: 1.9 m (6.2 ft)		