

## USE CASES:

Mail Server

Applicationserver

Backup Server

Analyse Station



# BOSTON FENWAY-T1XE34.2 (P3567)

## BUSINESS LINE

### HIGHLIGHTS:

MidiTower

Single Socket H5 (LGA-1200) supports Intel® Xeon® E-2300 and 10th Gen. Pentium® Processors

Dimensions (HxWxD):

424x193x525mm

Single 900W AC w/ PFC, 80 PLUS Gold Level Certified

### CONFIGURATION

(Individual adaptations possible)

#### CPU

1x Intel® Xeon® E-2314, 4-Core, 2.80GHz, 8MB L3-Cache, 65W (Rocket Lake-E)

#### MEMORY

2x 8GB (total 16GB) DDR4-3200, ECC, unbuffered

#### RAID CONTROLLER

SW-RAID 0, 1, 5, 10 support

### STORAGE DRIVES

1x 4.0TB SATA 6Gb/s, 7.200rpm, 3.5', 512e, Enterprise Capacity

### OPERATIONAL SYSTEM

Optional:

Microsoft® Windows™ Server

Red Hat Enterprise Standard Linux

### SUPPORT SERVICE

36 month (Bring In)

Optional:

36 month vor Ort 9/5 NBD



#### NETWORK

We have a large selection of different switch technologies as well as the matching transceivers. Contact our sales team, we will be happy to advise you.



#### LEASING

You can also lease all our hardware and services. Please contact our sales team sales team, we will be happy to advise you.



#### WORLDWIDE SUPPORT SERVICES

Our German-speaking after-sales support team is available to answer all your questions and provide warranty services.



Boston limited has been providing cutting edge technology since 1992 using Supermicro® building blocks, our high performance, mission-critical server and storage solutions can be tailored for each specific client, helping you to create your ideal solution.

From the initial specification, solution design and even full custom branding.

“WE CAN HELP YOU SOLVE YOUR TOUGHEST BUSINESS CHALLENGES SIMPLY AND EFFECTIVELY.”

**VISIT: BOSTON-IT.DE**

## TECHNICAL SPECIFICATIONS



MODEL	BOSTON FENWAY-T1XE34.2 (P3567)
CHIPSET	onboard Intel® C252
SOCKET	Single Socket H5 (LGA-1200) supports Intel® Xeon® E-2300 and 10th Gen. Pentium® Processors
MEMORY	max. 128GB of DDR4-3200 ECC unbuffered
LAN (onboard)	Dual Port 1000Base-T Network Adapter Intel® i210, 2x RJ45 AST2600 BMC (dedicated IPMI), 1x RJ45
GRAPHIC	onboard ASPEED AST2600 BMC, 1x VGA port
SAS / SATA / NVMe (onboard)	4x SATA 3.0 (6Gbs) ports 2x SATA 3.0 (6Gbs) SuperDOM ports SW-RAID 0, 1, 5, 10 support 1x M.2 port, PCI-E 3.0 x4, M-Key, Form Factor 2280/22110
POWER SUPPLY	Single 900W AC w/ PFC, 80 PLUS Gold Level Certified
REMOTE / IPMI	IPMI 2.0, remote KVM console w/ virtual media, power control, health values, dedicated LAN
INPUT / OUTPUT	onboard 2x COM ports (1x rear + 1x front)
USB	4x USB 2.0 (2x rear + 2x internal headers) 5x USB 3.2 Gen1 (2x rear + 2x front + 1x internal Type A)
TPM	onboard TPM 2.0 Header
EXPANSIONSLOTS	1x PCI-E 4.0 x8 (in x16 slot), 1x PCI-E 4.0 x8, 1x PCI-E 4.0 x4 (in x8 slot), 1x PCI-E 3.0 x2 (in x4 slot)
NO. MAX. HDD/SSD	4x 3.5" fixed SAS/SATA drive bays

All products and companies mentioned herein are trademarks or registered trademarks of their respective companies or trademark owners. #202111