



PremierColor coverage on this 27" monitor offers the ideal color space for every color professional.

Vivid, accurate colors and broad coverage of professional color standards

Dell PremierColor offers color professionals the tools they need for color-critical projects.

- Enjoy working with precise, accurate colors, factorycalibrated for quick set-up right out of the box with a small deltaE<2.
- Wide coverage of color industry standards including 100% Adobe RGB², 100% sRGB, 100% REC709, and 98% DCI-P3.
- Easy, user-enabled color adjustments plus extra precise calibration for custom palettes³ available via Dell UltraSharp Color Calibration Solution software⁹.
- Excellent range of color gamut and depth plus SDK / API for customizing Dell UltraSharp Monitors to your preferred in-house system.

Outstanding viewing experience

Ultra-thin bezels plus the crisp clarity of QHD resolution for an enhanced view of your work.

- Enjoy an almost seamless view with near-continual imagery across two or more monitors.
- Experience outstanding screen clarity with QHD resolution.
- Colors remain consistent across an ultra-wide viewing angle for a greater collaboration experience.
- Extensive digital connectivity including two HDMI 1.4/ MHL 2.0, four USB 3.0⁶ ports, DisplayPort 1.2¹ (in)/ mini-DisplayPort, DisplayPort (out- for multiple monitor setup), and two USB 3.0 upstream (KVM) ports.

Unmatched reliability

Comes with Dell's high reliability promise.


- Enjoy peace of mind from Dell's commitment to quality and customer satisfaction with the Premium Panel⁴
 Guarantee.
- Minimize downtime with Dell's 3-year Advanced Exchange Service⁷.
- Enjoy high reliability from the #1 monitor brand worldwide for two consecutive years*.

For more information visit www.dell.com/monitors

Thank you for making Dell Monitors
#1
worldwide*

Easily adjust the panel to your preferred viewing position.






Connectors



- AC Power
- HDMI/MHI В
- С DisplayPort (in)
- D Mini DisplayPort
- Е
- DisplayPort (out) Audio line-out
- G USB upstream (enable KVM)
- H USB downstream
- I Stand lock
- J Dell soundbar mounting slots



What's in the box?

Components

- Monitor panel
- Stand (riser and base)

Cables

- Power cable
- Mini-DisplayPort to DisplayPort
- USB 3.0 upstream

Documentation

- · Color calibration factory report
- Drivers and documentation media (CD)
- · Quick Setup Guide
- · Safety and regulatory information







- ¹ Dell PremierColor *Dell monitors are #1 Worldwide for 2 consecutive years. Source: NPD DisplaySearch Quarterly Desktop Monitor Shipment and Forecast Report (2013 and 2014). Ad#G15000115 **Registered in US and Canada only. ***Fepistered in US and Canada only. ***For charging BC1.2 devices and also supports up to 2A when powering standard USB devices.

- ***For charging BC1.2 devices and also supports up to 2A when powering standard USB devices.

 1 DisplayPort 1.2: Supports High Bit Rate 2 (HBR2) and Multi-stream transport (MST).

 2 AdobeRGB color gamut is based on CIE1931 test standard.

 3 Dell recommends optional X-Rite iDisplay Pro colorimeter for generating custom palettes. Optional and sold separately. You can purchase the X-Rite iIDisplay Pro colorimeter at Dell.com (select countries) or from any X-Rite online reseller.

 4 In the event you discover even one bright pixel on the Dell UltraSharp 27 Monitor during the Limited Hardware Warranty period, a free panel exchange is guaranteed. (see pixel panel info located on Dell.com web page for complete details): http://support.dell.com/support/topics/global.aspx/support/kcs/document?docid=414288

Dell UltraSharp 27 Monitor | UP2716D

Display	
Model number	UP2716D
Viewable image size (diagonal)	68.47 cm (27 inches)
Active display area	
Horizontal	596.74 mm (23.49 inches)
Vertical	335.66 mm (13.21 inches)
Maximum resolution	QHD 2560 x 1440 at 60 Hz
Aspect ratio Pixel pitch	0.2331 mm x 0.2331 mm
Brightness (typical)	300 cd/m² (min to max)
Color gamut (typical)	100% AdobeRGB ² , 100% sRGB, 100% REC709 and 98% DCI-P3 (delta E < 2)
Color depth	1.07 billion colors, 14-bit LUT
Contrast ratio (typical) Dynamic contrast ratio (typical)	1,000:1 (typical) 2 Million:1 (DCR)
Viewing angle (typical) (vertical/horizontal)	178°/178°
Response time (typical)	Fast mode: 6 ms gray-to-gray Normal mode: 14 ms gray-to-gray
Panel technology, surface	In-plane switching
Backlight	LED
Bezel color	Black
Connectivity	
Connectors	HDMI 1.4/ MHL 2.0 x 2, USB 3.0 ⁶ x 4, DisplayPort 1.2 ¹ (in)/ mini-DisplayPort, DisplayPort (out), USB 3.0 upstream (KVM) x 2.
Features	KVM (Keyboard, video, mouse), SDK
Dell soundbar (optional)	AC511
Design features	
Stand	Tilt, height adjustable stand, swivel, pivot clockwise and counter-clockwise, and built-in cable management
Security	Security lock slot (security lock not included)
VESA mounting support	100 mm x 100 mm
Power	
AC input voltage/frequency/current (typical)	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.6 A (maximum)
Power consumption (normal operation)	45W (typical); 40W (ENERGY STAR®)
Power consumption (active-off mode)	<0.3 W
Dimensions (with stand)	
Height (compressed ~ extended)	410.3 mm (16.15 inches) ~ 540.3 mm (21.27 inches)
Width	611.4 mm (24.07 inches)
Depth	200.3 mm (7.89 inches)
Weight	· · · · · · · · · · · · · · · · · · ·
Weight (panel only – no stand)	4.56 kg (10.05 lb)
Weight (with stand)	7.42 kg (16.36 lb)
Shipping weight	9.52 kg (20.99 lb)
omposition weight	5.52 ng (20.55 tb)
Standard service plan • 3 years Advanced Exchange Service ⁷	Environmental compliance ENERGY STAR®, EPEAT® Gold ⁵ , TCO Certified

- & Limited Hardware Warranty8
- Premium Panel Guarantee⁴

ENERGY STAR®, EPEAT® Gold⁵, TCO Certified Displays, China Energy Label, WEEE, ErP(EuP) Standards, Korea E-Standby

- $^{\rm 5}$ EPEAT Gold registered in the U.S. EPEAT registration varies by country. See www.epeat.net for
- EPEAT Gold registered in the U.S. EPEAT registration varies by country. See www.epeat.net for registration status by country.
 USB 3.0 does not support graphics output. USB 3.0 rate of data transfer can only be achieved with a computer that supports USB 3.0.
 Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.
 For a copy of the Limited Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see dell.com/warranty.
 Available for download from www.Dell.com/support.