

6x2 HDMI 10.2G Matrix with PiP Part No.: 38148



Description

- Switch between 6 HDMI source devices and output to 2 displays
- Supports resolutions up to 4K 30Hz 4:4:4
- PiP (Picture in Picture) allows for 1 main picture and 5 sub pictures on one display
- IR remote for easily switching between devices and displays
- 2 year warranty

The Lindy 6x2 HDMI 10.2G Matrix Switch with PiP allows for simple switching between 6 HDMI source devices and distributing to 2 displays, while also providing the ability to display all 6 sources on a single display using the PiP function.

Supporting HDMI 10.2G signals, this matrix allows for the transmission of detailed 4K Ultra HD resolutions, while HDCP 2.2 on input 1 and both outputs ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K media players.

The matrix also features PiP mode, which allows the user to generate multiple pictures on one display from the connected source devices, perfect for use in security, presentations with supporting data or collaborative working environments.

Please Note: When using DVI equipped devices with this HDMI splitter: To connect devices equipped with DVI connections, you can either use modular DVI/HDMI adapters or DVI/HDMI adapter cables. Please be aware that DVI is a "video only" interface, audio signals are not supported when using DVI devices.

Technical details

Specifications

- AV Interface: HDMI
- Interface Standard: HDMI 1.4
- Supports Bandwidth: 10.2 Gbps
- Maximum Resolution: 4096x2160@30Hz 4:4:4 8bit
- HDCP Support: 2.2
- Supported Audio:
 - Audio Pass-through
 - LPCM Audio Extraction
- IR Support : 30-60kHz
- CEC Support: Pass-Through (Port 1)
- Serial Interface: -
- LED / LCD Display: -
- Control: IR
- Special Features:
 - EDID Management
 - ARC Audio Extraction
 - Picture in Picture
 - \circ MHL

Connectors

- Input: 6 x HDMI (Female)
- Output: 2 x HDMI (Female), 3.5mm (Female), TOSLink Audio (Female)
- Control: -
- Power: 5.5/2.1mm DC socket

Physical Properties

- Dimensions WxHxD: 260x120x30mm (10.24x4.72x1.18in)
- Housing Material: Metal
- Nett Weight: 0.87kg (1.92lb)
- Operating Temperature : 0°C 40°C (32°F 104°F)
- Storage Temperature: -20°C 60°C (-4°F 140°F)
- Humidity: 20 90% (non-condensing)
- Power Requirements: 5VDC 2A
- Colour: Black

Miscellaneous

- Packaging Type: Carton box
- Packaging Dimensions: 305x240x60mm (12.01x9.45x2.36in)
- Gross Weight: 1.1kg (2.43lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH

Package Contents

• HDMI Matrix

- IR Remote Control
- Mounting Kit
- Multi-Country Power Supply (EU, UK, US & AUS)
- Lindy Manual

Purchasing Information

- No. 38148
- EAN: 4002888381482

© LINDY 2023