

# Product datasheet

Specifications



## Rack Side Air Distribution 2U 208/230 50/60HZ

ACF202BLK

### Overview

Presentation	Housing equipment with side to side airflow creates many challenges for IT and facility managers, particularly in regards to cooling. Because most enclosures are designed for a front to back airflow pattern, it is difficult to maintain ideal operating temperatures on side to side airflow equipment. The Rack Side Air Distribution Unit is a 2U rack mountable air distribution product for networking equipment or servers with side to side airflow. It pulls in conditioned air from the front of the rack and distributes it to the side air intake of the networking equipment.
--------------	--

Lead time

### Main

Main Input Voltage	200 V 208 V 230 V
Plug standard	IEC 60320 C13 IEC 60320 C14
Number of rack unit	2U
Number of cables	2
Provided equipment	Installation guide User manual

### General

Air flow	122.71 l/s
----------	------------

### Physical

Colour	Black
Height	8.7 cm
Width	43.1 cm
Depth	66.9 cm
Net weight	14.55 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Network frequency	50/60 Hz
-------------------	----------

### Conformance

Product certifications	cUL recognized
------------------------	----------------

CE  
GOST  
UL recognized

Communications & Management

Control panel                      Power on/off indicator

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	66 cm
Package 1 Length	78.7 cm
Package 1 Weight	19.509 kg

Offer Sustainability

EU RoHS Directive                      Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

Contractual warranty

Warranty                                      2 years repair or replace

Recommended replacement(s)