



HDMI to USB Type C Converter with USB Power

No.: 43347

Connects an HDMI source to a USB Type C equipped display

Description

- Connects an HDMI source to a USB Type C equipped display
- Supports resolutions up to 4K UHD 3840x2160@60Hz
- Supports 7.1 channel surround audio
- Integrated USB Power cable for use with low power HDMI sources
- 2 year warranty

The Lindy HDMI to USB Type C Converter allows the connection of HDMI source devices, such as a PC, Blu-ray player or media player to USB Type C equipped monitors, digital signage panels and LFDs (Large Format Displays). More and more displays are using the USB Type C connection, **and** this cable will allow you to harness the video capabilities from your HDMI source connection, to deliver astonishing quality to a range of displays such as ultra-thin monitors, portable screens, and touch panels as well as smartboards or portable projectors. Supporting resolutions up to 3840x2160@60Hz, this converter outputs content with superior clarity within innovative workspaces, engaging collaboration environments and educational setups. Immersive multi-channel audio is supported up to 7.1CH to compliment the video on screen.

For added convenience the converter features a USB power cable, allowing the converter to be externally powered when used with low power HDMI sources. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient plug & play installation.

Technical details

Specifications

- AV Interface: HDMI to USB Type C
- Interface Standard: HDMI 2.0 / USB Type C with DisplayPort 1.2 Alternate Mode
- Supported Bandwidth: 18Gbps
- Maximum Input Resolution: 3840x2160@60Hz 4.4:4 8bit SDR
- Maximum Output Resolution: 3840x2160@60Hz 4.4:4 8bit SDR
- Chipset: LTD6711A
- HDCP Support: HDCP 1.4
- Supported Audio: Supports 7.1 LPCM 192kHz 24bit
- Separate Audio Ports: -
- Special Features: Optional power via USB

Connectors

- Input:
 - HDMI Type A Male
 - USB Type A Male for optional power
- Output: USB Type C Female

Physical properties

- Dimensions (approx.) WxDxH:
 - Housing: 54.5x42x13.6mm (2.15x1.65x0.54in)
 - HDMI: 23x19.1x8.5mm (0.9x0.75x0.33in)
 - USB: 18x13.6x6.72mm (0.7x0.54x0.26in)
- Cable Length: USB: 300mm (11.81in); HDMI: 135mm (5.31in)
- Housing Material: Aluminium
- Jacket Material: PVC
- Jacket Diameter: HDMI: 5.2mm (0.2in), USB: 3.5mm (0.14in)
- Minimum Bend Radius: 48mm (1.89in)
- Net Weight: 0.043kg (0.09lb)
- Operating Temperature: 0°C to 45°C (32°F - 113°F)
- Storage Temperature: -10°C to +80°C (14°F - 176°F)
- Humidity: 10 - 85% RH (non-condensing)
- Colour: Grey

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x20x194mm (6.3x0.79x7.64in)
- Gross Weight: 0.07kg (0.15lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH, CP65

Package Contents

- HDMI to USB Type C Converter with USB Power
- Lindy manual

Purchasing Information

- No.: 43347
- EAN: 4002888433471