

Eaton EVMIF132A

Catalog Number: EVMIF132A

Eaton Metered Input G4 Rack PDU, 0U, 39U, IEC-60309 input, 3m cord, 1ph, 7.4kW, 32A, 200-240V, 24 outlets (12)C13, (12)C39

General specifications



Product Name

Eaton Rack PDU G4

Catalog Number

EVMIF132A

Model Code

PDU G4 MI 0U 309 32A 1P
12xC13,12xC39

EAN

3553340697173

UPC

786689801359

Product Length/Depth

1000 mm

Product Height

53 mm

Product Width

52 mm

Product Weight

3.8 kg

Compliances

FCC part 15 class A
CAN ICES-003 class A
CB
LVD Directive
RoHS Directive
WEEE Directive
Packaging Directive

Certifications

cTUVus
UL 62368-1
IEC 62368-1
EN IEC 63000
CISPR 35/EN 55035
CE
EAC
UKCA
Cm
Ukr
IEC/EN 61000-6-2
IEC/EN 61000-6-4
IEC 61000-3-11
IEC 61000-3-12

Product specifications

Electrical connection

Connecting cord with plug

Wattage

7.4 kW max

Form factor

0U (Vertical)

Mounting direction

Vertical

Number of Outputs 6-20R

0

Number of Outputs C20

0

Amperage Rating

32 A

Input connection

IEC-60309 32A 1Ph

Num of Outputs PC (SCHUKO)

0

Number of Outputs L14-30R

0

Frequency rating

50/60 Hz

Evaluation

At distance

Operating Temperature

0° to 60°C (32° to 140°F)

Number of outlets with earth pin

24

No of Outlet Suisse Stndrd Type25

0

Mass configuration

Yes

No of Outlet Suisse Stndrd Type23

0

Special features

Resources

Brochures

Rack PDU G4 Brochure EN

Declarations of conformity

EU declaration of conformity Rack PDU G4

Drawings

EVMIF132A-en-US

Remote Site Management

Versatile C39 outlet
supports C14 or C20 power
cord plug

High retention outlets
designed to securely fit
standard power cords and
support P-Lock power cords

Cybersecurity standards UL
2900-1 and IEC 62443-4-2

Hot-Swap network control
module

Network Cascading, connect
up to 32 PDUs via network
loop

Power sharing between two
network modules PDUs
ensures constant access to
PDU data & sensors

1% IEC Class 1 billing grade
measurement accuracy

Gigabit network card with 2x
Gb ports

Support protocols RestAPI,
Modbus TCP, SNMP, LDAP,
HTTPS

Optional sensor

Temperature/Humidity

Cord length

3m

Number of Outputs 6-15R

0

Color

Black

SNMP

Yes

Over voltage category

2

Outlets

(12) C13, (12) C39

Number of Outputs L6-30R

0

Number of Outputs 5-20R

0

Number of UK BS1363 sockets

0

Number of Outputs 5-15R

0

Number of Outputs L5-30R

0

No of Outlet Suisse Stndrd Type15

0

Number of Outputs C13

12

No of Outlet Suisse Stndrd Type13

0

Phase

Single-phase

Mounting dimension (standardized)

Metric

Accessories

Rack PDU

Rack mounting accessories

Quickstart guide

Safety Instructions

Number of outputs hardwired

0

Number of outputs (other)

12

Ethernet interface

Yes

Number of Outputs C19

12

Outlet control

No

Switchable

No

Input voltage

200-240V

Material

Aluminium

Number of Outputs L6-20R

0

Series

G4

Type

Metered input Rack PDU

Serial interface

Yes

Mounting Dimension (metrical)

52

Number of Outputs L5-20R

0



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia