



# Item No. 87694 Delock Displayport 1.2 Splitter 1 x Displayport in > 4 x Displayport out 4K

### Description

This splitter by Delock receives a Displayport signal from a PC or laptop and splits it to four connected displays. Thereby one Displayport connection can be used to operate four Displayport monitors. The outputs are dual-mode capable (DP++), so that HDMI or DVI monitors can be connected with suitable adapters.



### Specification

- Connectors: Input:
- 1 x Displayport 20 pin male
- 1 x 5 V DC jack
- Output:
- 4 x Displayport 20 pin female
- Chipset: STDP4320
- Displayport 1.2a specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Maximum resolution (depending on the system and the connected hardware): Displayport 1.1 or 1.2 Single Stream Transport (SST): up to 1920 x 1080 @ 60 Hz (mirror) Displayport 1.2 Multi Stream Transport (MST): up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (mirror or extended)
- max. 4x 1920 x 1080 @ 60 Hz
- Displayport output supports Dual Mode DP++
- · Supports audio and video signals
- Supports Eyefinity / Single Large Surface (SLS)
- · Audio input formats: 7.1 channel up to 192 kHz sample rate
- Metal housing
- Cable length without connectors: ca. 30 cm
- Colour: black
- Dimensions (LxWxH): ca. 143 x 67 x 23 mm
- OS independent, no driver installation necessary

## Power supply specification

- Wall power supply
- Input: AC 100  $\sim$  240 V / 50  $\sim$  60 Hz / 0.4 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions: inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm

length: ca. 9 mm

System requirements

One free Displayport female

# © 2017 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

# Additional Information

EAN: 4043619876945

Country of origin: Taiwan, Republic of China

Package: Retail Box







# Package content

- Displayport Splitter
- External power supply
- User manual

## Images



DATASHEET



General	
Specification:	Displayport 1.2a
Interface	
Output:	4 x Displayport 20 pin female
Input:	1 x Displayport 20 pin male
	1 x 5 V DC female 5,5 mm x 2,1 mm
Technical characteristics	
Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Physical characteristics	
Housing material:	metal
Cable length incl. connector:	30 cm
Length:	143 mm
Width:	67 mm
Height:	23 mm
Colour:	black
Power supply	
Туре:	Euro wall power supply
Connector:	DC male 5.5 mm x 2.1 mm