



#### Fanfold or roll media

The CL-S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

#### Easy read LCD panel

The LCD panel allows quick and simple configuration and also flashes red when an error occurs quickly alerting the operator.

#### Environmentally friendly

From production and packaging to utilisation and recycling the CL-S400DT fulfills today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

## CL-S400DT

### Label, Ticketing

#### Applications

- Courier
- Retail
- Logistic / Transport
- Ticketing
- Kiosk
- Betting



Performance ticket and label printing

TOMORROW'S PRINTING TODAY



With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

### Specifications

|                              |                                                                                                                                                    |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                        | CL-S400DT                                                                                                                                          |
| Printing Technology          | Direct Thermal                                                                                                                                     |
| Resolution                   | 203 dpi                                                                                                                                            |
| Print Speed (maximum)        | 6 inches per second (150 mm/s)                                                                                                                     |
| Print Width (maximum)        | 4 inches (104 mm)                                                                                                                                  |
| Media Width (min to max)     | 0.5 - 4.6 inches (12.5 - 118 mm)                                                                                                                   |
| Roll Size (max), Core Size   | Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)                                                       |
| Media Thickness (min to max) | 63.5 to 254 µm                                                                                                                                     |
| Media Length (min to max)    | 0.25 to 32 inches (6.35 to 812.8 mm)                                                                                                               |
| Media Sensor                 | Fully adjustable gap, notch and reflective black mark                                                                                              |
| Main Interface               | Dual Interface Serial (RS-232C), USB (version 2.0, full speed)                                                                                     |
| Optional interfaces          | Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant) |
| Mechanism                    | Hi-Lift™ metal mechanism with wide opening head                                                                                                    |
| Control panel                | 4 buttons, 16x2 LCD with 2-colour backlight and sophisticated menu configuration system                                                            |
| Emulations (Languages)       | Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , CBI™ BASIC Interpreter, Eltron® EPL2®           |
| Drivers and software         | Free-of-charge from website, including support for various platforms                                                                               |
| Flash (Non-Volatile Memory)  | 8 MB total, 1 MB available for user                                                                                                                |

Size (W x D x H) and Weight 206 x 149 x 150mm, 2.68 Kg (excluding roll holder)

## CL-S400DT

### Label, Ticketing

### Features & Benefits

- Paper load: Durable design - Citizen's proven Hi-Lift™ all-metal mechanism
- Printing Speed: Fast print out - 6 inches per second (150 mm per second)
- Media support: Versatile Media Support - Fanfold media stacks and roll paper support
- Display: 2-colour LCD display enables intuitive operation
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Basic peeler