



## Item No. 87693

# Delock Displayport 1.2 Splitter 1 x mini Displayport in > 4 x Displayport out 4K

#### Description

This splitter by Delock receives a Displayport signal from a PC or laptop and splits it to four connected displays. Thereby one Displayport connection can be used to operate four Displayport monitors. The outputs are dual-mode capable (DP++), so that HDMI or DVI monitors can be connected with suitable adapters.



## **Specification**

· Connectors:

Input:

1 x mini Displayport 20 pin male

1 x 5 V DC jack

Output:

- 4 x Displayport 20 pin female
- · Chipset: STDP4320
- Displayport 1.2a specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Maximum resolution (depending on the system and the connected hardware):

Displayport 1.1 or 1.2 Single Stream Transport (SST):

up to 1920 x 1080 @ 60 Hz (mirror)

Displayport 1.2 Multi Stream Transport (MST):

up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (mirror or extended)

max. 4x 1920 x 1080 @ 60 Hz

- Displayport output supports Dual Mode DP++
- · Supports audio and video signals
- Supports Eyefinity / Single Large Surface (SLS)
- Audio input formats: 7.1 channel up to 192 kHz sample rate
- · Metal housing
- Cable length without connectors: ca. 30 cm
- Colour: black
- Dimensions (LxWxH): ca. 143 x 67 x 23 mm
- · OS independent, no driver installation necessary

## Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.4 A
- Output: 5 V / 2 A
- · Ground outside, plus inside
- · Dimensions:

inside: ø ca. 2.1 mm

outside: ø ca. 5.5 mm

length: ca. 9 mm

#### System requirements

One free mini Displayport female

### Additional Information

EAN: 4043619876938

Country of origin: Taiwan, Republic of

China

Package: Retail Box








## Package content

- Displayport Splitter
- External power supply
- User manual

## **Images**









| General                       |                                   |
|-------------------------------|-----------------------------------|
| Specification:                | Displayport 1.2a                  |
| Interface                     |                                   |
| Output:                       | 4 x Displayport 20 pin female     |
| Input:                        | 1 x mini Displayport 20 pin male  |
|                               | 1 x 5 V DC female 5,5 mm x 2,1 mm |
| Technical characteristics     |                                   |
| Chipset:                      | STDP4320                          |
| Maximum screen resolution:    | 3840 x 2160 @ 30 Hz               |
| Physical characteristics      |                                   |
| Housing material:             | metal                             |
| Cable length incl. connector: | 30 cm                             |
| Length:                       | 143 mm                            |
| Width:                        | 67 mm                             |
| Height:                       | 23 mm                             |
| Colour:                       | black                             |
| Power supply                  |                                   |
| Type:                         | Euro wall power supply            |
| Connector:                    | DC male 5.5 mm x 2.1 mm           |