



APC NetShelter Rack PDU Advanced, Switched Metered Outlet, 7.4kW, 1Phase, 230V, 32A, 332P6, 40 Outlet

APDU10150SM

Overview

Lead Time

Main

| Colour | Black |
|---------------------------|-------------------------|
| Product Or Component Type | PDU |
| Pdu Type | Switched metered outlet |
| Cord Length | 3.0 m |

Complementary

| Input Voltage | 230 V 3 phases | |
|--|--|--|
| Height | 149.0 cm | |
| Width | 5.6 cm | |
| Output Voltage | 230 V | |
| Depth | 7.5 cm | |
| Net Weight | 7.5 kg | |
| Mounting Location | Side | |
| Mounting Preference | No preference | |
| Input Plug Type | IEC 60309 32 A 2P + PE | |
| Mounting Mode | Rack-mounted | |
| Rack Units | 0U | |
| | | |
| Mounting Position | Vertical | |
| Mounting Position Communication Port Protocol | Vertical 1000BASE-T 10/100BASE-T | |
| | 1000BASE-T | |
| Communication Port Protocol | 1000BASE-T 10/100BASE-T | |
| Communication Port Protocol [In] Rated Current | 1000BASE-T 10/100BASE-T 32 A | |
| Communication Port Protocol [In] Rated Current Permissible Voltage | 1000BASE-T 10/100BASE-T 32 A 200240 V | |
| Communication Port Protocol [In] Rated Current Permissible Voltage Input Current Limits | 1000BASE-T 10/100BASE-T 32 A 200240 V 32 A | |

Environment

| Product Certifications | UKCA TAA compliance | |
|---------------------------------------|------------------------|--|
| Standards | CE EN 62368-1 | |
| Ambient Air Temperature For Operation | -560 °C | |
| Relative Humidity | 595 % | |
| Operating Altitude | 010000 ft | |
| Ambient Air Temperature For Storage | -2565 °C | |
| Storage Relative Humidity | 595 % | |
| Storage Altitude | 0.00 15240.00 m | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 172 cm |
| Package 1 Width | 11.6 cm |
| Package 1 Length | 20.8 cm |
| Package 1 Weight | 9.5 kg |

Contractual warranty

Warranty 3 years repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |