

Rittal – The System.

Faster – better – everywhere.

Overvoltage protection PSM – DK 7856.170

Date : Jul 5, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Overvoltage protection PSM – DK 7856.170

created: 05.07.2021 on www.rittal.com/com-en



Product description

Design:	Overvoltage protection type 3
Description:	Connected upstream of the busbar. An overvoltage protection is available for each 3-phase infeed to the busbar. The overvoltage protection may also be retrofitted.
Note:	One adaptor is required for each infeed.

Product description

Connector:	Wago X-Com
Sockets:	Wago X-Com
Rated operating voltage:	230 V
Infeeds:	Phases per infeed: 3~
Rated current (max.):	16 A
Packs of:	1 pc(s).
Weight/pack:	0.82 kg
Copper weight (kg per piece):	0
EAN:	4028177402621

Customs tariff number:	85369001
ETIM 7.0:	EC000942
ETIM 6.0:	EC000942
eCl@ss 8.0/8.1:	27130806
eCl@ss 6.0/6.1:	27142604
Product description:	DK PSM Overvoltage protection, Wago X-Com
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity