

Rittal – The System.

Faster – better – everywhere.

CMC III Processing Units – DK 7030.000

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CMC III Processing Units – DK 7030.000

created: 12.07.2021 on www.rittal.com/com-en



Product description

Description:	Central unit of the CMC III monitoring system. In addition, up to 32/4 external sensors/CAN-Bus connection units may be connected additionally to the integral sensors.
Benefits:	High redundancy due to redundant power supply. Cost saving due to optimised space utilisation and connection technique High flexibility due to modular system. High reliability due to permanent monitoring of the physical enclosure parameters.
Equipment:	Piezo signal generator for acoustic information Time function thanks to real-time clock with NTP
Applications:	Enclosure monitoring in IT, industry and facility management
Function principle:	Central monitoring unit for the CMC III system. Collates measurement data and alerts network management systems or control rooms when freely adjustable limit values are exceeded. Automatic regulation of actuators and control of remote outputs.
Material:	Plastic
Surface finish:	Front: Smooth Enclosure: Textured
Colour:	Enclosure: RAL 7035 Front: RAL 9005
Protection category IP to IEC 60 529:	IP 30
Supply includes:	Basic system Temperature sensor including connection cable (supplied loose)

Infrared access sensor (integrated)
Assembly parts for mounting on surfaces

Note: Unencrypted protocols may be deactivated for enhanced network security

Product description

Number of sensors (max.): 32

Dimensions: Width: 138 mm
Height: 40 mm
Depth: 132 mm

Rated operating voltage: 24 V (DC)

Number of sensors (max.): 32

Installation dimensions: Installation depth: 120 mm
Build depth: 12 mm

Operating temperature: Operation (environment): +0 °C...+45 °C

Ambient humidity (non-condensing): Operation (environment): 5 % - 95 %

Equipment (electrical): Integral infrared access sensor (max. sensing distance 100 mm): yes
Integral temperature sensor: yes

Protocols: TCP/IPv4
TCP/IPv6
SNMPv1
SNMPv2c
SNMPv3
Telnet
SSH
FTP
SFTP with SSL
HTTP
HTTPS with SSL
NTP
DHCP
DNS
SMTP
Syslog
LDAP
Radius
OPC-UA
Modbus/TCP
RS-232

Equipment SSC: LED displays (front): Status
LED displays (rear): Network status

Interfaces/connections: General: Mini USB
General: 1 x USB
General: SD memory card slot (max. 32 GB)

General: 2 digital inputs
 Network: Ethernet to IEEE 802.3 via 10/100BaseT full-duplex, 10/100 Mbit/s, PoE
 Serial: RJ12
 Bus system: 2 x RJ45 CAN bus
 Length per CAN bus (max.): 50 m
 Alarm relay output: Terminal up to 1.5 mm² (max. 24 V DC/1 A)
 Redundant power supply: Terminal
 Redundant power supply: Jack
 Redundant power supply: PoE (Power over Ethernet)
 Streaming: Axis network camera with VAPIX® version 3
 Mobile website: For Android and Windows phones

Packs of:	1 pc(s).
Weight/pack:	0.62 kg
Copper weight (kg per piece):	0
EAN:	4028177659322
Customs tariff number:	85311095
ETIM 7.0:	EC002627
ETIM 6.0:	EC002627
eCl@ss 8.0/8.1:	27189253
eCl@ss 6.0/6.1:	27189253
Product description:	DK CMC III Processing Unit, Central unit of the CMC III monitoring system, WHD: 138x40x132 mm, max. 32 sensors
Approvals	
Approvals:	UL + C-UL
Certificates:	BITMi EAC IEC
Declarations:	FCC