

# DATASHEET

Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm<sup>2</sup>



## General data

Plug IEC60320/C20 to jack IEC60320/C19  
16 A / 250 V VDE tested

## Allgemeine Daten

Number of cores	3
Colour outer sheath	black
Spiralized cable	False
With cord switch	False
Material outer sheath	Polyvinyl chloride (PVC)

## Mechanische Eigenschaften

Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female

## Kabelmantel

Temperature resistance	0 - 70 °C
------------------------	-----------

## Elektrische Eigenschaften

Protective conductor	True
Nominal voltage	250 V

## Normen, Zulassungen, Zertifizierungen

This datasheet was created automatically on 03-07-2023 . Technical changes reserved.



# DATASHEET

## Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm<sup>2</sup>

Oil resistant (acc. EN 60811-2-1) | False

### Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length Leiternennquerschnitt Außendurchmesser ca.		
EK519.1	Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm <sup>2</sup>	black	1.0 m	1,50 mm <sup>2</sup>	8,6 mm
EK519.1,8	Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm <sup>2</sup>	black	1.8 m	1,50 mm <sup>2</sup>	8,6 mm
EK519.2,5	Extension Cable C20 180° - C19 180°, Black, 2.5 m, 3 x 1.50 mm <sup>2</sup>	black	2.5 m	1,50 mm <sup>2</sup>	8,6 mm
EK519.5	Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm <sup>2</sup>	black	5.0 m	1,50 mm <sup>2</sup>	8,6 mm

This datasheet was created automatically on 03-07-2023 . Technical changes reserved.

