

Product data sheet

Specifications



APC Power-Saving Back-UPS Pro 1500, 1500VA, 230V, LCD, 6 Schuko CEE 7 outlets (3 surge)

BR1500G-GR

Overview

Lead time

Main

Main Input Voltage	230 V
Rated power in W	865 W
Rated power in VA	1500 VA
Nb of power socket outlets	3 Schuko CEE 7 3 Schuko CEE 7 surge
Cable length	1.52 m

General

Provided equipment
telephone cable
user manual
USB cable
warranty card

Number of power module free slots
0

Number of power module filled slots
0

Redundant
No

Physical

Height
30.1 cm

Width
11.2 cm

Depth
38.2 cm

Net weight
13 kg

Mounting preference
No preference

Mounting mode
Not rack-mountable

Two post mountable
0

USB compatible
No

Input

Network frequency
50 Hz +/- 1 Hz
60 Hz +/- 1 Hz

Input voltage limits	156...300 V adjustable 176...294 V
-----------------------------	---------------------------------------

Output

Maximum configurable power in W	865 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	1500 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Product certifications	BSI 1363 CE NEMKO
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	1
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery charger power	23 W rated
Battery power in VAh	187 VAh runtime
Battery life	3...5 year(s)
Battery option	BR24BPG 1 518 VAh
Extended runtime	0

Communications & Management

Control panel	Multifunction LCD status and control console
----------------------	----------------------------------------------

Surge Protection and Filtering

Surge energy rate	441 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line) RJ45 modem/fax/DSL protection (four wire dual line)

Packing Units

Package 1 Weight	13.8 kg
Package 1 Height	39 cm
Package 1 width	23.5 cm
Package 1 Length	49 cm
SCC14	10731304286872
Number of Units in Package 3	20

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	-----------------------------------------------------------------------------------