

# Rittal – The System.

Faster – better – everywhere.

## **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7721.535**

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7721.535

created: 07.12.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



Product description	
Design:	Pre-configured
Description:	Wall-mounted enclosure with optimum accessibility due to hinged part.
Material:	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	IP 54 in conjunction with solid gland plate, top and bottom
IK Code:	IK08
Supply includes:	Wall section with solid gland plate at the top and brush strip at the bottom, two vertical mounting rails and C rail, horizontal, for cable clamping Hinged part with 25 mm pitch pattern of holes in the front and rear frame, two 482.6 mm (19") mounting angles at the front, infinitely depth-variable, and side outlet filters on the left and right Earth rail with star earthing Designer glazed door 1 double-kit key no. 5 Wall mounting bracket, 10 mm, reinforced Comfort handle for lock inserts and 2-point locking Security lock 3524 E
Basic material:	Sheet steel

## Product features

<b>Dimensions:</b>	Width: 600 mm Height: 1012 mm Units: 21 U Depth: 673 mm
<b>Depth hinged part:</b>	516 mm
<b>Installation depth:</b>	620 mm
<b>Clearances:</b>	Clearance width: 502 mm Clearance height: 949 mm
<b>Wall section:</b>	Depth: 135 mm
<b>Load capacity:</b>	Hinged part, static (max.): 750 N
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	61 kg
<b>EAN:</b>	4028177551039
<b>Customs tariff number:</b>	94032080
<b>ETIM 7.0:</b>	EC000261
<b>ETIM 6.0:</b>	EC000261
<b>eCl@ss 8.0/8.1:</b>	27142408
<b>eCl@ss 6.0/6.1:</b>	27180208
<b>Product description:</b>	DK Wall-mounted enclosures, 3-part, WHD: 600x1021x673 mm, 21 U, Pre-configured, with mounting angles, depth-variable

## Approvals

<b>Approvals:</b>	UL + C-UL
<b>Certificates:</b>	EAC IK-Code Protection category
<b>Declarations:</b>	Declaration of conformity