INFORMATION



49" curved VA Dual QHD monitor with USB-C dock, KVM and 5MP webcam for easier multitasking

Work with multiple applications, large spreadsheets or detailed documents on one screen. The 49" ProLite XCB4997DQSNPH delivers the workspace of two QHD monitors without a bezel in between, so you can organise your work and keep key information in view. The 1000R curved VA panel brings the entire 5120 x 1440 workspace into a more natural field of view, while 120Hz keeps scrolling smooth and fluid.

One USB-C cable carries video, data, LAN and up to 95W charging, cutting down on cables and adapters. The built-in KVM switch lets you use one keyboard and mouse with two computers, while Screen Split allows your computer to recognise the monitor as two independent QHD displays. The integrated 5MP webcam with microphone and Windows Hello support lets you join video calls and sign in securely without extra equipment.




Curved for immersive viewing

Step into an immersive, natural viewing setup that minimizes distortion and reduces eye strain during long work or entertainment sessions.



Easy access with Windows Hello cam

Log in quickly and securely with facial recognition, while enjoying crystal-clear video calls thanks to the high-resolution autofocus webcam.



Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.



USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable — handle video, data, and power while keeping your desk clean and organized.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	curved, 3-side borderless
Diagonal	49", 124cm
Panel	VA LED, matte finish
Curved	1000R
Native resolution	5120 x 1440 @120Hz (7.4 megapixel DQHD)
Aspect ratio	32:9
Panel brightness	400 cd/m²
Static contrast	3000:1
Advanced contrast	80M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln (sRGB: 100%; NTSC: 80%)
Horizontal Sync	30 - 185kHz
Viewable area W x H	1191.9 x 335.2mm, 46.9 x 13.2"
Pixel pitch	0.233mm
Frame Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.1) DisplayPort x1 (v.1.4) USB-C x1 (PD 95W)
USB HUB	x4 (2x Type-A v.3.2 Gen 1 (5Gbps, 4.5W), 2x Type-C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, USB v.3.2 (Gen 1, 5Gbit))
HDCP	yes
RJ45 (LAN)	x1

03 FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	i-Style Colour, PiP, PbP, Screen Split (MST Dual-Screen), built-in 5MP webcam with autofocus, microphone and privacy shutter compliant with Windows Hello
HDR	ready, HDR10
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Navigation (power) button: Center (Main Menu/Execution), Front (Move Down/N/A), Back (Move Up/Input Select), Right (Move Right/Volume), Left (Move Left/Submenu)

User controls	picture adjust (brightness, contrast, ECO, ACR, OD, HDR, Adaptive Sync, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp., user preset), PiP/PbP (PiP/PbP, sub source, PiP position, PiP size, swap, audio input), KVM, MST Dual-Screen, Webcam, OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB-C speed, USB update), input select, audio settings (volume, mute), recall (recall all?)
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, tilt
Height adjustment	130mm
Tilt angle	21° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.8m), DP (1.8m), USB-C (1.0m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	45W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	G
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	Lead, Decabromodiphenylethane

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	1150.5 x 434.5 (564.5) x 356mm
Box dimensions W x H x D	1290 x 485 x 370mm
Weight (without box)	11.9kg
Weight (with box)	23kg
EAN code	4948570128006


4-M4 x 10 SCREW HOLE
(VESA MOUNT)
100.0
11.5
275.0
265.0
550.0
1150.5
253.0
152.0
387.5
397.0
422.5
410.5 (MIN)
434.5 (MAX)
265.5
221.0
40.0

GALLERY



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**