OVERVIEW





| 1. Power button | 11. Serial * |
|--|---------------------------------------|
| 2. Card reader * | 12. VGA |
| 3. Microphone (3.5mm) | 13. 2x USB 2.0 |
| 4. Headphone / microphone combo jack (3.5mm) | 14. 1x USB 3.2 Gen 1 |
| 5. USB-C 3.2 Gen 1 (data transfer, 15W charging) | 15. 1x USB 3.2 Gen 1 (smart power on) |
| 6. 2x USB 3.2 Gen 1 | 16. Kensington Security Slot |
| 7. Optical drive * | 17. Ethernet (RJ-45) |
| 8. Audio line-out (3.5mm) | 18. Smart cable clip slots * |
| 9. HDMI 2.1 TMDS | 19. Serial * |
| 10. DP 1.4 | 20. Optional ports * |
| | |

Notes:

• Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® Celeron®, Intel Pentium®, or 12th / 13th Generation Intel Core™ i3 / i5 / i7 Processor

Processor**

| Processor Name | Cores | res Threads Base Frequency | | Max Frequency | Cache | Memory Support | Processor Graphics |
|---|-----------------------------|---|----------------------------------|---|---------------------------|-------------------|---------------------------|
| Celeron G6900 | 2 | 2 | 3.4GHz | - | 4MB | DDR4- 3200 | Intel UHD Graphics 710 |
| Pentium Gold G7400 | 2 | 4 | 3.7GHz | - | 6MB | DDR4- 3200 | Intel UHD Graphics 710 |
| Core i3-12100 | 4 (4 P-core + 0 E-core) | 8 | P-core 3.3GHz | P-core 4.3GHz ^[1] | 12MB | DDR4- 3200 | Intel UHD Graphics 730 |
| Core i3-12300 | 4 (4 P-core + 0 E-core) | 8 | P-core 3.5GHz | P-core 4.4GHz ^[2] | 12MB | DDR4- 3200 | Intel UHD Graphics 730 |
| Core i5- 12400 | 6 (6 P-core + 0 E-core) | 12 | P-core 2.5GHz | P-core 4.4GHz ^[3] | 18MB | DDR4- 3200 | Intel UHD Graphics 730 |
| Core i5-12500 | 6 (6 P-core + 0 E-core) | 12 | P-core 3.0GHz | P-core 4.6GHz ^[4] | 18MB | DDR4- 3200 | Intel UHD Graphics 770 |
| Core i5- 12600 | 6 (6 P-core + 0 E-core) | 12 | P-core 3.3GHz | P-core 4.8GHz ^[5] | 18MB | DDR4- 3200 | Intel UHD Graphics 770 |
| Core i7-12700 | 12 (8 P-core + 4 E-core) | 20 | P-core 2.1GHz / E-core 1.6GHz | Max Turbo up to 4.9GHz / P-core 4.8GHz / E-core 3.6GHz ^[6] | 25MB | DDR4- 3200 | Intel UHD Graphics 770 |
| Core i3-13100 4 (4 P-core + 0 E-core) 8 P-6 | P-core 3.4GHz | P-core 4.5GHz ^[7] | 12MB | DDR4- 3200 | Intel UHD Graphics 730 | | |
| Core i5- 13400 | 10 (6 P-core + 4 E-core) | 16 | P-core 2.5GHz / E-core 1.8GHz | P-core 4.6GHz / E-core 3.3GHz ^[8] | 20MB | DDR4- 3200 | Intel UHD Graphics 730 |
| Core i5-13500 | 14 (6 P-core + 8 E-core) | 20 | P-core 2.5GHz / E-core 1.8GHz | P-core 4.8GHz / E-core 3.5GHz ^[9] | 24MB | DDR4- 3200 | Intel UHD Graphics 770 |
| Core i5- 13600 | 14 (6 P-core + 8 E-core) | 20 | P-core 2.7GHz / E-core 2.0GHz | P-core 5.0GHz / E-core 3.7GHz ^[10] | 24MB | DDR4- 3200 | Intel UHD Graphics 770 |
| Core i7-13700 16 (8 P-core + 8 E-core) 24 P-core 2.1GHz / E-core 1.5GHz | | Max Turbo up to 5.2GHz / P-core 5.1GHz / E-core 4.1GHz ^[1] | 30MB | DDR4- 3200 | Intel UHD Graphics 770 | | |

Notes:

[1], [2], [3], [4], [5], [6], [7], [8], [9], [10], [11] Intel Max Turbo frequency will vary depending on application workload and the hardware and software configurations, see

http://www.intel.com/technology/turboboost/ for more information.

Operating System

Operating System**

- Ubuntu Linux^[1]
- Windows® 11 DG Windows 10 Pro 64
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 Pro
- No operating system

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel RST RAID, Human Presence Detection, etc.

Graphics

Graphics**[1]

| Graphics | Туре | Memory | Connector | Max Resolution | Key Features |
|---------------------------|------------|--------|--|---|-----------------|
| Intel UHD graphics 710 | Integrated | Shared | 1x HDMI® 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2 | 3840×2160@60Hz(HDMI), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP) | DirectX® 12 |
| Intel UHD graphics 730 | Integrated | Shared | 1x HDMI 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2 | 3840×2160@60Hz(HDMI), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP) | DirectX 12 |
| Intel UHD graphics 770 | Integrated | Shared | 1x HDMI 2.1 TMDS, 1x VGA, 1x DP 1.4 HBR2 | 3840×2160@60Hz(HDMI), 1920x1200@60Hz(VGA), 4096x2304@60Hz(DP) | DirectX 12 |

Notes:

[1] The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section).

Monitor Support

Monitor Support

Supports up to 3 independent displays via (HDMI, DP and VGA)

Chipset

Chipset

Intel B660 chipset

Memory

Max Memory^[1]

Up to 64GB DDR4-3200

Memory Slots

Two DDR4 UDIMM slots, dual-channel capable

Memory Type

DDR4-3200

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Storage Support^[1]

Up to two drives, 1x 3.5" HDD + 1x M.2 SSD

- 3.5" HDD up to 2TB
- M.2 SSD up to 1TB

Storage Type***

| Disk Type | Interface | RPM | Security | |
|---------------|--------------------------|------|----------|--|
| 3.5" SATA HDD | SATA 6Gb/s | 7.2K | - | |
| M.2 2280 SSD | PCIe® NVMe®, PCIe 4.0 x4 | - | Opal | |
| M.2 2280 SSD | PCIe NVMe, PCIe 4.0 x4 | - | Opal 2.0 | |

Notes:

[1] The max capacity of each disk type is based on the test results with current Lenovo storage offerings.

Removable Storage

Optical**

PSREF Product Specifications Reference

- DVD-ROM, SATA 1.5Gb/s, slim (9.0mm)
- DVD burner (DVD±RW), SATA connector, slim (9.0mm)

None

Card Reader

- 7-in-1 card reader (SD, SDHC, SDXC, MMC, MS, MS-Pro, XD)
- No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC623-CG codec

Speakers

- No speakers
- Single speaker, 1W x1

Power Supply

Power Supply**

| Power | Туре | Efficiency | Key Features |
|-------|-------|------------|---|
| 180W | Fixed | 85% | Autosensing |
| 260W | Fixed | 90% | Autosensing, 80 PLUS Platinum qualified |

DESIGN

Input Device

Keyboard**

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Traditional Keyboard (USB connector), black
- No keyboard

Mouse

- Lenovo Calliope Mouse (USB connector), black
- No mouse

Mechanical

Form Factor

SFF (7.4L)

Dimensions (WxDxH)^[1]

100 x 308 x 274.8 mm (3.9 x 12.1 x 10.8 inches)

Packaging Dimensions (WxDxH)

195 x 390 x 500 mm (7.7 x 15.4 x 19.7 inches)

Weight^[2]

Around 4.5 kg (9.9 lbs)

Packaging Weight

Around 6.35 kg (14 lbs)

Case Color

Raven black

Bays

- 1x 2.5"/3.5" disk bay
- 1x slim ODD bay

Expansion Slots

- One PCIe 4.0 x16, low-profie (length < 167.65mm, height < 68.90mm)
- One PCIe 3.0 x1, low-profie (length < 167.65mm, height < 68.90mm)
- Two M.2 slots (one for WLAN, one for SSD)

Stand

Vertical stand

Lenovo

• No stand

Others

(Optional) Smart Cable (USB-A to USB-C®)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Onboard Ethernet

Gigabit Ethernet, Realtek RTL8111HN, 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth®**

- Intel Wi-Fi[®] 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1 (Bluetooth 5.2 hardware ready), M.2 Card^[1]
- Realtek Wi-Fi 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Intel Wi-Fi 6E AX211, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1 (Bluetooth 5.3 hardware ready), M.2 Card^[2]
- No WLAN and Bluetooth

Notes:

[1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

[2] Bluetooth 5.3 is hardware ready but may run at a lower version due to OS limitations.

Ports^[1]

Front Ports

- 1x USB-C 3.2 Gen 1 (support data transfer and 5V@3A charging)
- 2x USB 3.2 Gen 1
- 1x headphone / microphone combo jack (3.5mm)
- 1x microphone (3.5mm)

Optional Front Ports

1x card reader

Rear Ports

- 2x USB 2.0
- 2x USB 3.2 Gen 1 (one supports Smart Power On)
- 1x HDMI 2.1 TMDS
- 1x DisplayPort[™] 1.4
- 1x VGA
- 1x Ethernet (RJ-45)
- 1x line-out (3.5mm)

Optional Rear Ports***

- 2x USB 2.0
- 1x parallel
- 1x serial
- 1x 2nd serial
- None

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s.

Monitor Cable

Monitor Cable***

- HDMI to HDMI cable (1.5m)
- HDMI to VGA dongle
- DP to VGA dongle
- DP to DVI dongle
- DP to dual DP dongle
- DP to HDMI dongle
- No monitor cable

SECURITY & PRIVACY

Security

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

- (Optional) Smart Cable Clip
- Kensington[®] Security Slot[™], 3 x 7 mm
- Padlock Loop

Chassis Intrusion Switch

- Chassis intrusion switch
- No chassis intrusion switch

Fingerprint Reader

No fingerprint reader

BIOS Security

- Secure Wipe
- Power-on password
- Supervisor password
- Hard disk password
- Certificate based BIOS authentication
- Certificate based BIOS management
- Cover presence switch
- Self-healing BIOS
- Smart USB protection (allows keyboard / mouse only, blocks all storage devices)
- Intel BIOS guard

MANAGEABILITY

System Management

System Management

Non-vPro®

SERVICE

Warranty^{III}

Base Warranty**

- 1-year courier or carry-in service
- 1-year limited onsite service
- No base warranty

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <u>https://smartfind.lenovo.com/</u>. To learn more details of warranty policy, please access <u>https://pcsupport.lenovo.com/warranty</u>.

Operating Environment

Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications^{III}

Green Certifications

- (Optional) ENERGY STAR[®] 8.0
- (Optional) EPEAT[™] Gold Registered^[2]
- (Optional) EPEAT Silver Registered^[3]
- ErP Lot 3
- RoHS compliant
- TCO Certified

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or selfdeclaration.

[2], [3] EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

Other Certifications

Other Certifications

- (Optional) TÜV Rheinland[®] Low Noise
- (Optional) TÜV Rheinland Ultra Low Noise
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

ThinkCentre neo 50s Gen 4



intel

Lenovo

PSREF Product Specifications Reference



intel



intel



intel



intel