

UA9 Thin Client

Workforce Mobility
Simplified



IGEL | Ready



**Built Durable, Built for
the Mobile Workforce**

The fanless UA9 eliminates moving components, ensuring unmatched durability and dependability for your mobile workforce



**Efficiency that Saves the
Day—and Your Budget**

Equipped with the Intel® Alder Lake CPU, UA9 slashes electricity costs, reduces e-waste, and extends its operational lifespan—all while delivering exceptional performance



**Stay Connected,
Stay Productive**

Built-in WiFi, wired connectivity, and support for two UHD/4K displays create a seamless, immersive workspace for mobile teams



**Big Screen,
Big Results**

UA9's 15.6-inch LCD screen and Numpad keyboard are designed for productivity, making it ideal for intensive mobile work environments

UA9 Thin Client

Workforce Mobility Simplified



Performance

CPU	Intel® Alder Lake N100 processor supports up to 3.4GHz max boost frequency, Quad Core
Memory	8GB DDR4-3200MHz single channel
Multiple Display	15.6" full HD LCD, 1 HDMI , USB-C
Display Resolution	Full HD on LCD, 4K 60Hz on connected display (Max)
Brightness (typical)	250 cd/m ² typ.
Viewing Angle	CR(>10):85/85 (V/H) typ.
Graphic & Multimedia	<ul style="list-style-type: none"> Intel® 12th UHD Graphics 24EUs Full HD 2MP webcam with microphone HEVC, VP9, and AVC decode support Support AVX2 instruction sets

Expandability

WiFi	<ul style="list-style-type: none"> Onboard combo WiFi6, 2 internal antenna (RTL8852BE) Bluetooth 5.2
Storage	<ul style="list-style-type: none"> M.2 2280 M Key 128GB SATA SSD Micro SD Card Reader
LAN	RJ-45 10/100/1000Mbps
USB	3 USB-A 3.2 Gen1, 1 USB-C 3.2 Gen1 with DP Alt mode, power delivery
Audio & Sound	Combo audio jack for headset & Internal speakers
Power	USB Type-C 65W power adapter
Battery	Polymer 3S1P 11.4V/3950mAh/45W Li-Polymer Battery, 3 cells
Keyboard Language	German, Spanish, French, English, Dutch

Security / Manageability

Security Lock	Security lock 3*7mm
WoL	RJ45 LAN with standby power design supports Magic Packet wake-up event
TPM	Infineon TPM 2.0

Environment

Cooling	Passive cooling (Noise-Free)
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F
Operating Humidity	20% - 80% non-condensing

Physical

Dimension (w x h x d) & Weight:
244 x 21.6 x 368mm / 1.8kg

Note: UltrArmor may update or modify information, products, or programs without prior notice.