

# Product datasheet

Specifications



## Rack PDU, Basic, Zero U, 32A, 230V, (20)C13 & (4)C19

AP7553

### Overview

Lead time

### Main

<b>Main Input Voltage</b>	200 V 208 V 230 V
<b>Main Output Voltage</b>	230 V
<b>Input Connection Type</b>	IEC 60309 32 A 2P + E
<b>Number of rack unit</b>	0U
<b>Cable length</b>	3.05 m
<b>Number of cables</b>	1
<b>Provided equipment</b>	Installation guide Rack mounting brackets Toolless mounting kit

### Physical

<b>Colour</b>	Black
<b>Height</b>	161.9 cm
<b>Width</b>	5.6 cm
<b>Depth</b>	4.4 cm
<b>Net weight</b>	5.57 kg
<b>Mounting location</b>	Side
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted

### Input

<b>Input current limits</b>	32 A
<b>Load capacity</b>	7400 VA
<b>Network frequency</b>	47...63 Hz

### Output

<b>Number of power socket outlets</b>	20 IEC 60320 C13 4 IEC 60320 C19
---------------------------------------	-------------------------------------

## Conformance

Product certifications	CE VDE
------------------------	-----------

## Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	212.1 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	6.466 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------