



Active holder for fixed installation

With USB-A cable. 2 USB-A ports: QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt.

Item no: 727334

EAN Number: 7320287273342

Keep your phone's battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. For fixed installation. The holder is to be connected inside the dashboard, providing an elegant installation without any cables hanging over the interior. The charging box has two USB -A ports: QC 3.0A + 2.4A. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the phone in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 2A fuse. Professional installation recommended. Attach onto a ProClip mounting platform.

Fits the following models:

Honeywell CT30XP
Honeywell CT37

For a complete list, see
www.brodit.com/en/product/727334

Measurements:

Height 106 mm
Width 84 mm
Depth 56 mm
Volume 499 cm³
Weight 272 g

Charging specifications:

- Input Molex 2-Pin
- Output Connector Type: Dual USB Type-A Female.
- Output Voltage: 5V, 9V, 12V(Nominal)
- Output Current:
- USB Port 1: QC3.0. 3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A (Recommended for Android etc)
- USB Port 2: 4.9V ~ 5.25V 2.4A (Recommended for Apple)
- Output Voltage Ripple: 300mV pk-pk at Max Load
- Input Voltage Range: DC 12--24V DC, Input can handle 40V Load dump transient events
- Input Current: 3.0 A DC Max
- Input Current with No device attached: 0.005A
- DC-DC Conversion Efficiency: Over 86% Typical
- Rated Power:
- USB Port 1: 18 Watts Max.
- USB Port 2: 12 Watts Max.