K280e Corded Keyboard

logitech

Logitech K280e Corded Keyboard delivers optimal typing with an ultra-durable build, resulting from years of research. With a comfortable palm rest, ultra-silent keys, a breakfree chassis and abrasion-resistant keys, it offers years of productivity designed for today's workplace.

PRODUCT BENEFITS

OPTIMAL TYPING THROUGH RESEARCH

- Full-size layout, generous palm rest
- 19mm pitch, 2.2mm key travel, 106mm spacebar
- Ultra-silent keys (<45 dB)
- Personalized comfort: 0° flat angle or 8° tilt angle

ULTRA-DURABLE BUILD

- Heavy duty, break-free chassis with reinforced steel
- Long life UV-coated, abrasion-resistant keys, designed to last over 20 million keystrokes
- Spill resistant up to 60mls
- 3 year warranty

PRODUCTIVITY DESIGNED FOR TODAY'S WORKFORCE

- Modern styling: ultra-flat with framed keys and premium finishing
- USB plug-and-play simplicity works right out of the box, no software required
- Bright LED status notification lights for Caps, Scroll and Number lock
- 104 keys with 13 hot keys for media controls and productivity shortcuts

SPECIFICATIONS

Certification	GS GS CE CE CE CFC FCC C-Tick C VCCI C			
Compatibility	Windows (XP, 7, 8, 10 and later)			
Spill Resistant	YES			
Warranty	3 years			
Service Life	20 million key operations per key			
Key Print (Durability)	Tampo + UV coating			
Connectivity	USB			
Profile	Ultra-flat			
Tilt Legs	YES			
Tilt Angles	0° flat or 8° tilt			
Keyboard Layout	Standard			
Palm Rest	YES			
Battery Life	Corded			
Media Hot Keys	13 Media Hot Keys			
Illuminated Caps Lock	YES			
Illuminated Num Lock	YES			
Number Pad	YES			
Number of Keys	104 including 13 Function integrated hot keys			
Cable Length	Cable 1,8 m			
Product Weight	930 g			
Dimensions (W x D x H)	459 x 182 x 20 mm			
Total weight (with packaging)	1105 g			
Packaging dimensions	482 x 188 x 27 mm			
Storage Temperature	-40°C to 70°C			
Operating Temperature	0°C to 40°C			
	Typ.16mA			
Current Consumption	Typ.16mA			
Current Consumption Reliability	Typ. 16mA MTTF* > 150,000 hours *Mean Time To Failure of electrical components			
	MTTF* > 150,000 hours *Mean Time To Failure of electrical			
Reliability	MTTF* > 150,000 hours *Mean Time To Failure of electrical components DEU, CH, UK, PAN-NORDIC, FRA,			
Reliability Layout	MTTF* > 150,000 hours *Mean Time To Failure of electrical components DEU, CH, UK, PAN-NORDIC, FRA, RUS, US INT'L, ITA Master package: 10			
Reliability Layout Packaging Unit	MTTF* > 150,000 hours *Mean Time To Failure of electrical components DEU, CH, UK, PAN-NORDIC, FRA, RUS, US INT'L, ITA Master package: 10 Pallet: 60			

K280e Corded Keyboard

logitech

Product Name	Part Number	EAN Code	Keyboard Layout	Product Color
K280e Corded Keyboard	920-005209	5099206046771	UK English	Black
K280e Corded Keyboard	920-005210	5099206046788	French	Black
K280e Corded Keyboard	920-008669	5099206076679	German DIN 2137:2012-06 DIN EN ISO 9241-4/-410	Black
K280e Corded Keyboard	920-005214	5099206046825	Italian	Black
K280e Corded Keyboard	920-005215	5099206046832	Russian	Black
K280e Corded Keyboard	920-005216	5099206046849	Pan Nordic	Black
K280e Corded Keyboard	920-005217	5099206046856	US International	Black
K280e Corded Keyboard	920-005218	5099206046863	Swiss	Black



© 2016 Logitech. Logitech, Logi and other Logitech marks are owned by Logitech and may be registered. Microsoft, Windows and the Windows logo are trademarks of the Microsoft group of companies. Linux is a registered trademark of Linus Torvalds. All other trademarks are the property of their respective owners.