



Delock Adapter Displayport 1.2 male > HDMI female 4K 60 Hz Active

Description

This adapter by Delock enables the connection of an HDMI monitor to your system via a free Displayport interface. The adapter supports a resolution up to 4K Ultra HD at 60 Hz and is backward compatible to Full-HD 1080p. The adapter offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.



ltem No. 62734

EAN: 4043619627349

Country of origin: China

Package: Retail Box



Specification

- Connector: Displayport 20 pin male > HDMI-A 19 pin female
- Chipset: Parade PS176
- Displayport 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Active converter, for graphics cards with DP and DP++ output
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transfer of audio and video signals
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Supports Eyefinity
- · Supports HBR2 (5.4 Gbps) data rate
- Audio formats: 8-channel LPCM, compressed audio and HBR audio format up to 24 Bit audio sample size and 192 kHz sample rate
- Gold-plated connector
- 1 x ferrite core
- Cable length without connector: ca. 20 cm
- · Colour: black
- · OS independent, no driver installation necessary

System requirements

A free Displayport female port

Package content

Adapter Displayport to HDMI

Images







General	
Specification:	Displayport 1.2
	High Speed HDMI with Ethernet
	HDCP 1.4
	HDCP 2.2
Supported operating system:	OS independent, no driver installation necessary
Interface	
Output:	1 x HDMI-A 19 pin female
Input:	1 x Displayport 20 pin male
Technical characteristics	
Chipset:	Parade PS176
Converter type:	active
Maximum screen resolution:	4096 x 2160 @ 60 Hz
Signal transmission:	video
	audio
Physical characteristics	
Ferrite core:	1 x
Cable length:	20 cm
Connector finishing:	gold-plated
Colour:	black