

Product datasheet

Specifications



APC Parallel Maintenance Bypass Panel, up to 3 units 30-40kVA, 400V Wallmount

SBPAR30K40H-WP

Overview

Lead time

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in VA	120000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Provided equipment	Installation guide User manual

Physical

Height	117.4 cm
Width	56 cm
Depth	21.6 cm
Net weight	53 kg
Mounting support	Wall
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50 Hz
-------------------	-------

Conformance

Standards	EN 50091-2 EN/IEC 62040-3 EN/IEC 62040-1-1 VFI-SS-111
-----------	--

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...9144.00 m

Batteries & Runtime

Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	129.8 cm
Package 1 Width	70.4 cm
Package 1 Length	33.5 cm
Package 1 Weight	54.885 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Recommended replacement(s)