

ML1050STi

Ultra-compact short throw LED projector



- **HD Ready and LED technology** - Great for movies, gaming and PC-free presentations
- **Short throw lens with auto focus**
- **Feature packed** - Built-in media player, optional wireless, HDMI, microSD and built-in speaker
- **Ultra compact and lightweight** - only 420g

The ML1050STi is a compact and versatile projector designed for various scenarios. Whether you're in a business meeting, presenting on-the-go, or enjoying movies at home, this tiny powerhouse weighs just 420g and comes with a convenient carry bag.



Specifications

EAN: 5055387668317, Colour: White+Gray

UPC: 796435 44 744 1, Colour: White+Gray



Display/image

| | |
|---------------------------------------|-------------------------------------|
| Display technology | DLP™ |
| Resolution | WXGA (1280x800) |
| Brightness (HK/ANSI) | 1000/535 |
| Contrast ratio | 20,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 4:3, 16:9 |
| Keystone correction - vertical | +/-40° |
| Has vertical auto keystone correction | Yes |
| Horizontal scan rate | 15.375 ~ 91.146Khz |
| Vertical scan rate | 24 ~ 85(120 for 3D)Hz |
| Uniformity | 90% |
| Screen size | 1.27m ~ 2.54m (50" ~ 100") diagonal |

Lamp info

| | |
|-------------------|--------------|
| Light source type | LED |
| LED life | 20,000 hours |

Optical

| | |
|-------------------------|---------------|
| Throw ratio | 0.8:1 |
| Projection distance (m) | 0.86m - 1.72m |
| Zoom type | Fixed |
| Focal length (mm) | 8.02mm/0.32" |
| Native offset | 100% |

Connectivity

| | |
|-------------|--|
| Connections | Inputs 1 x HDMI 1.4b, 1 x microSD card, 1 x USB-A reader Outputs 1 x Audio 3.5mm Control 1 x RS232 (via mini USB connector) |
|-------------|--|

General

| | |
|--------------------------------|--|
| Noise level (min) | 22dB |
| Noise level (max) | 29dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) |
| 3D compatibility | SVGA 120Hz, XGA 120Hz |
| 3D | 3D ready |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish |
| 24/7 operation | Yes |
| Operating conditions | 0°C~40°C/41°F~95°F, max altitude 2500M/8202.5ft, max humidity 85% |
| Remote control | Card style |
| Speaker count | 1 |
| Watts per speaker | 2W |
| In the box | Carry bag Universal I/O cable AC power cord Remote control 1x CR2032 Battery Basic user manual 1x RS232 Mini-USB adaptor |
| Operating system compatibility | Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ |
| Input lag | 16.00ms |
| Optional wireless models | EZC-USB |

Power

| | |
|-----------------------------|-----------------------|
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 23W |
| Power consumption (max) | 67W |

Weight and dimensions

| | |
|---------------------------|----------------|
| Dimensions (W x D x H) mm | 112 x 123 x 57 |
| Gross weight | 1.2 kg |
| Net weight | 0.4 kg |

