Fujitsu recommends Windows 11 Pro.

FUJITSU

Data Sheet Fujitsu Tablet LIFEBOOK U9312X

World's Lightest Convertible With A Pen

Available in red and black, the Fujitsu LIFEBOOK U9312X is an attractively slim and lightweight 360-degree convertible. All-day battery runtime and global LTE ensure highest productivity in any place. Enterprise-grade security such as the integrated PalmSecure[™] sensor, powerful performance and utmost connectivity via Intel[®] Thunderbolt[™] 4 ensure best-in-class user experience.

Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing just 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel[®] Iris[®] Xe Graphics

Security at its best

No compromises in security and data protection – the integrated PalmSecure[™] sensor turns your unique palm vein pattern into your personal key.

- Privacy Camera Shutter to keep external eyes away
- PalmSecure[™] as your personal biometrical key
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display supporting pen input
- Pen garage with inductive charging function
- 5 MP rear camera

Convenient mobility supporting usage on the go

- Highest productivity on business trips without empty batteries or waste of time
- New advanced battery with improved runtime that extents your mobile working sessions
- Anytime USB charging functionality for your peripheral devices, even when system is turned off
- Always connected and instantly ready









Components

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home	
Operating system compatible	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home	
Microsoft OS support information	After the end of the product life Fujitsu will continue to test and support all upcoming Windows releases for a period of maximum 5 years, depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows General Availability Channel" at https://support. ts.fujitsu.com/IndexProdSupport.asp?Ing=com&OpenTab=	
Operating system notes	The use of Windows Operating Syste applicable under the relevant Micros	m is subject to acceptance of the End User License Agreement of Microsoft as soft program.
Processor	Intel Core i7-1265U/32GB vPro (10 C	ores, up to 4.8 GHz)
	Intel Core i7-1265U/16GB vPro (10 C	ores, up to 4.8 GHz)
	Intel [®] Core [™] i5-1245U processor (10	Cores, up to 4.4 GHz)
	Intel® Core™ i5-1235U processor (10	Cores, up to 4.4 GHz) *
	*Processor only for retail, SMB, education of the second s	ation and government
Memory	8 GB onboard memory LPDDR4 16 GB onboard memory LPDDR4 32 GB onboard memory LPDDR4	
	No DIMM	
LCD Display	13.3" Full-HD (1920x1080) AG Touch	
Bluetooth	V5.2	
Hard disk drives (internal)	PCIe-SSD, 512 GB M.2 NVMe module	, SED
	PCIe-SSD, 256 GB M.2 NVMe module	, SED
	PCIe-SSD, 2 TB M.2 NVMe module, SI	D
	PCIe-SSD, 1 TB M.2 NVMe module, SI	D
Hard disk notes	Accessible capacity may vary, also de	epending on used software.
Interface add on cards/components (optional)		
3G/4G (optional)	Quectel EM120R-GL (4G Cat.12) (Dov	vnlink speed 600 MB/s, Uplink speed 150 MB/s)
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x	1,080 pixel, Anti-glare touchscreen, 400 cd/m², 1000:1
Multimedia		
Camera	Front: IR Cam (2 MP) with LED, suppo Out camera: 5 MP with autofocus on	

Base unit

Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red	
General system information			
Chipset	Integrated in CPU		
Supported capacity RAM (min.)	8 GB		
Supported capacity RAM (max.)	32 GB		
Memory slots	LPDDR4		

General system information				
Memory notes	8 GB / 16 GB / 32 GB onboard			
	LPDDR4x (4,266 MHz)			
	Dual channel support			
LAN	10/100/1,000 MBit/s Intel® I219LM			
LAN notes	Intel vPro support			
Integrated WLAN	Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2			
BIOS version	UEFI Specification 2.8			
BIOS features	InsydeH2O BIOS			
Audio type	On board			
Audio codec	Realtek ALC257			
Audio features	2x digital array microphones, 2x built-in speakers (stere	20)		
MIL-STD tested				
Color	Black	Red		
Material	Magnesium	Magnesium		
Display				
Diagonal Size	33.8 cm (13.3-inch)			
Display Technology	IPS			
Display type	Anti-glare touchscreen			
Display Resolution type	FHD			
Resolution (native)	1,920 x 1,080 pixel			
Aspect ratio	16:9			
Brightness - typical	400 cd/m ²			
Contrast - typical	1000:1			
Viewing angle (h/v) - typical	178°/178°			
Display notes	Wide-view high-bright LED display (for enhanced outd	oor viewing). With magnesium display lid.		
Sensors	3-axis Accelerometer			
	Gyroscope Magnetic Field Sensor Compass			
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10	finger multi-touch screen		
Pen	AES			
	4k pressure level Pen garage inductive charging			
Graphics				
Base unit	LIFEBOOK U9312X black	LIFEBOOK U9312X red		
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz	up to 4,096 x 2,160 @ 60 Hz		
Graphics brand name	Intel [®] Iris [®] Xe Graphics (with Dual channel memory)	Intel [®] Iris [®] Xe Graphics (with Dual channel memory)		
Graphics features	4 Display Support (3 external, 1 internal) HDCP support DirectX [®] 12 OpenGL [®] 4.5	4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5		
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator			
Interfaces				
DC-in	1			
Audio: line-out / headphone	1 (combo port with audio line-in)			
Audio: line-in / microphone	1 (combo port with Audio line-out)			
Internal microphones	2x digital array microphones			
USB 3.2 Gen1 (5 Gbps) total	2x Type-A (1 with Anytime USB charging functionality)			
USB 4.0 Gen3 (20 Gbps) total	2 x Type-C Intel® Thunderbolt™4 (with Power Delivery f	unctionality)		

2 USB 4 Gen3 Thunderbolt [™] 4, Power Delivery (15W), DP	1.4	
1		
1 (USH-II) SD 4.0 standard SD/microSD card: 2GB SDHC/microSDHC card: 32GB SDXC/microSDXC card: 2TB		
1		
1 (Nano-SIM, only for models with integrated 4G/LTE mo	dule)	
eSIM supported - integrated in 4G/LTE Module		
USB Type-C		
1		
USB Type-C PR	Thunderbolt™ 4 PR	
	1 (20V/170W required)	
1	1	
1 Combo jack for headset usage	1 Combo jack for headset usage	
1x V1.2	2x V1.4++	
1		
1	V 2.0b	
3x Type-A - 5V/0.9A, 4.5W 1x Type-C - 15W 1x Type-C - Up to 60 W (PD v2.0-1.1) power output to client or 4.5W input	2x Type-A - 5V/0.9A, 4.5W 1x Type-A - 5V/2.4A, 12W 2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A upstream (PC), Intel AMT support (vPRO) 1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A downstream, power output to client	
no	1	
1	1 (10/100/1000 Mbit/s, 2,5 Gbps)	
Number of simultaneous used displays and its possible resolutions and frequencies depend on mobile system and display interface type. Please consult always also the manual of the connected client.		
Backlit keyboard w/o touchstick		
Number of keyboard keys: 85, Keyboard pitch: 19 mm, Ke	eyboard stroke: 1.5 mm	
Multi gesture touchpad with integrated mouse button fu Touchscreen Tablet Pen (AES), stored in pen garage	unctionality	
2x dual band for WLAN, 2x for LTE, Bluetooth shared with WLAN		
V5.2		
Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2		
WPA/WPA2/WPA3 (Wi-Fi Protected Access)		
WiFi 6E is supported by Windows 11 OS only - Windows 10 OS supports WiFi 6 only. Import and usage according to country-specific regulations.		
LTE Quectel EM120R-GL (Cat 12) - UMTS,LTE		
Including GPS functionality Import and usage according to country-specific regulations. LTE Connection Manager (if configured with 4G/LTE)		
Import and usage according to country-specific regulation	ons.	
Import and usage according to country-specific regulation	ons.	
Import and usage according to country-specific regulation LTE Connection Manager (if configured with 4G/LTE)	ons.	
	1 (USH-II) SD 4.0 standard SD/microSD card: 2GB SDHC/microSDXC card: 2TB Speed Class: up to UHS-II (156MB/s) 1 1 (Nano-SIM, only for models with integrated 4G/LTE mo eSIM supported - integrated in 4G/LTE Module USB Type-C 1 USB Type-C PR 1 (19V/90W required) 1 1 Combo jack for headset usage 1 x V1.2 1 1 3 x Type-A - 5V/0.9A, 4.5W 1 x Type-C - 15W 1 x Type-C - 15W 2 x dual band for WLAN, 2x for LTE, Bluetooth shared with V5.2 Intel Wi-Fi 6E AX211 & BT5.2 vPro, SRD Cat. 2 WPA/WPA2/WPA3 (Wi-Fi Protected Access) WiFi 6E is supported by Windows 11 OS only - Windows 1 Import and usage according to country-specific regulatio LTE Quectel EM120R-GL (Cat 12) - UMTS,LTE	

Power supply			
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	
·	(grounded) Type-C AC-Adapter standard	(grounded) Type-C AC-Adapter standard	
AC adapter	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C	19 V / 65 W (3.42 A) 20 V / 65 W (3.25 A) Type C	
Notes	65W AC adapter for usage with system/ min. 90W AC Ac	lapter for usage with Port Replicator	
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
1st battery	Lithium polymer battery 4-cell, 64 Wh	Lithium polymer battery 4-cell, 64 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	11 h	11 h	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	309 x 214.8 x 16.9 mm		
	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Weight (lbs)	2,23 lbs		
Weight notes	Weight may vary depending on actual configuration		
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)		
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80%	(relative humidity)	
Product	LIFEBOOK U9312X		
Europe	CE CB		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Adobe [®] Reader [®] (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft [®] Office 365 customers. Buy Microsoft Office.)		
Additional software (optional)	Recovery DVD for Windows [®] Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc [™]) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)		
Additional software (notes)	Use of accopanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.		
Manageability			
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 15.0 (depending on processor)		

Manageability	
Manageability software	DeskView Client
	DeskView Instant BIOS Management
DeskView components	Inventory Management
	BIOS Management
	Driver Management
	Security Management
	Alarm Management
Supported standards	WMI (Windows Management Instrumentation)
	PXE (Preboot Execution Environment)
	DMI (Desktop Management Interface)
	SMBIOS (System Management BIOS)
	WBEM (Web Based Enterprise Management)
	CIM (Common Information Model)
	BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Absolute Persistence [®] technology capable BIOS
	Optional: Trusted Platform Module (TPM 2.0)
	EraseDisk
User Security	Hard disk password
	User and supervisor BIOS password
	Embedded fingerprint sensor (optional)
	Embedded PalmSecure™ sensor (optional)
	Smartcard reader (integrated)
	AuthConductor Client Basic (secure authentication solution)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security.
	However, these properties are not sufficient on their own to protect the product from all existing threats, such as
	intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use
	the configuration options as available for the respective product. During operation, the IT security of this product
	is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a
	manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices
	and/or general product operation.

Packaging information

Warranty		
Warranty period	2 years (for countries within EMEIA)	
Warranty type	Bring-in Service / Collect & Return Service (depending on country)	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu. com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support Services - the perf	ect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	5 years after end of product life	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/	

Recommended Accessories

Thunderbolt [™] 4 Port Replicator	First Thunderbolt [™] Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	Order Code: FPCPR401BP
USB Type-C Port Replicator 2	Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	Order Code: S26391-F3327-L100
USB Type-C AC Adapter	Recharge your notebook or tablet at work, at home or on the road with this USB Type-C power source easily.	Order Code: S26391-F3326-L502
AES Pen with replacement stylus tips	Take your creativity to the next level, with the most natural pen experience with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen.	
Car Adapter USB-C-QC	One Car Adapter fits all. Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrand- independent notebooks and all mobile devices. The Car Adapter USB-C- QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung charge.	Order Code: S26391-F2613-L630

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9312X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9312X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

https://www.fujitsu.com/emeia/products/ computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/ navigation/terms-of-use.html Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-06-01 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/ navigation/terms-of-use.html

Copyright 2022 Fujitsu Technology Solutions GmbH