

# Rittal – The System.

Faster – better – everywhere.

## FlatBox – DK 7507.020

Date : Dec 7, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# FlatBox – DK 7507.020

created: 07.12.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

|                         |   |
|-------------------------|---|
| <b>Design:</b>          | with 482.6 mm (19") mounting frame  |
| <b>Description:</b>     | For flexible use as a wall-mounted or floor-standing enclosure.   |
| <b>Benefits:</b>        | Tool-free quick assembly<br>System assembly on the open 482.6 mm (19") frame  |
| <b>Material:</b>        | Sheet steel<br>Viewing window: Single-pane safety glass, 3 mm   |
| <b>Surface finish:</b>  | Powder-coated   |
| <b>Colour:</b>          | RAL 7035  |
| <b>Supply includes:</b> | Flat-packed enclosure<br>1 wall section<br>2 basic supports<br>2 roof/base plates, with cut-outs for cable entry via brush strips<br>2 side panels, lockable<br>1 glazed door, lockable, security lock 3524 E, door hinge point selectable<br>Connection components for tool-free, fast assembly<br>Earthing kit for system-compatible earthing of all enclosure parts<br>482.6 mm (19") mounting frame |
| <b>Note:</b>            | Max. installation depth: Depth - 58 mm to rear panel<br>Max. distance between two 482.6 mm (19") levels: Depth - 104 mm   |
| <b>Basic material:</b>  | Sheet steel   |

## Product features

|  |   |
|--|---|
| <b>Dimensions:</b>                         | Width: 600 mm<br>Height: 625 mm<br>Depth: 400 mm                          |
| <b>Installation height for components:</b> | 12 U  |
| <b>Load capacity:</b>                      | max. 600 N  |
| <b>Packs of:</b>                           | 1 pc(s).  |
| <b>Weight/pack:</b>                        | 26.45 kg  |
| <b>EAN:</b>                                | 4028177551411   |
| <b>Customs tariff number:</b>              | 94032080  |
| <b>ETIM 7.0:</b>                           | EC002500  |
| <b>ETIM 6.0:</b>                           | EC002500  |
| <b>eCl@ss 8.0/8.1:</b>                     | 27180208  |
| <b>eCl@ss 6.0/6.1:</b>                     | 27180208  |
| <b>Product description:</b>                | DK FlatBox, WHD: 600x625x400 mm, 12 U, with 482.6 mm (19") mounting frame |
| <b>Approvals</b>                           |   |
| <b>Certificates:</b>                       | EAC   |