


OVERVIEW



| | |
|--------------------------------------|--|
| 1. Pen slot * | 6. 2x Thunderbolt 4 |
| 2. Nano-SIM card slot (WWAN model) * | 7. USB-A (USB 5Gbps), Always On |
| 3. USB-A (USB 5Gbps) | 8. Headphone / microphone combo jack (3.5mm) |
| 4. HDMI | 9. Smart card reader * |
| 5. Kensington Nano Security Slot | |

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 PRO 200 Series Processor

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics | NPU | Overall TOPS |
|-------------------------------------|-------|---------|----------------|---------------|------------------|--------------------|------------------------------|---------------|
| AMD Ryzen™ 3 PRO 210 | 4 | 8 | 3.0GHz | 4.7GHz | 4MB L2 / 8MB L3 | AMD Radeon™ 740M | - | - |
| AMD Ryzen™ 5 PRO 215 | 6 | 12 | 3.2GHz | 4.7GHz | 6MB L2 / 16MB L3 | AMD Radeon™ 740M | - | - |
| AMD Ryzen™ 5 PRO 230 ^[1] | 6 | 12 | 3.5GHz | 4.9GHz | 6MB L2 / 16MB L3 | AMD Radeon™ 760M | AMD Ryzen™ AI, up to 16 TOPS | Up to 31 TOPS |
| AMD Ryzen™ 7 PRO 250 | 8 | 16 | 3.3GHz | 5.1GHz | 8MB L2 / 16MB L3 | AMD Radeon™ 780M | AMD Ryzen™ AI, up to 16 TOPS | Up to 38 TOPS |

Notes:

[1] AMD Ryzen™ 5 PRO 230 is for special bid only.

AI (Artificial Intelligence)

AI PC Category

AI PC (models with AMD Ryzen™ 7 PRO 250 processor)^[1]

NPU

Integrated AMD Ryzen™ AI, up to 16 TOPS^[2]

Notes:

[1] AI PCs have a NPU capable of 10+ TOPs to run the Copilot assistant by pressing the optional Microsoft® Copilot key or using Win + C.

[2] Only for the models with AMD Ryzen™ 7 PRO 250 processor.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux^[1]
- No preload operating system

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics**

| Graphics | Type | Memory | TGP | Key Features |
|------------------|------------|--------|---------------|--------------|
| AMD Radeon™ 740M | Integrated | Shared | Share CPU TDP | DirectX® 12 |
| AMD Radeon™ 760M | Integrated | Shared | Share CPU TDP | DirectX® 12 |
| AMD Radeon™ 780M | Integrated | Shared | Share CPU TDP | DirectX® 12 |

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 3840x2160@60Hz

- Thunderbolt™ supports up to 5120x2880@60Hz

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory

- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5x-7500^[1]

Notes:

[1] Installed memory is actually LPDDR5x-8533 but runs as LPDDR5x-7500 due to platform limitation.

Storage

Max Storage Support^[1]

One drive, up to 1TB M.2 2242 SSD

Storage Slot^[2]

One M.2 2242 PCIe® 4.0 x4 slot

Storage Type

| Disk Type | Interface | Offering | Security |
|--------------|---------------------------|---------------------|----------|
| M.2 2242 SSD | PCIe® NVMe®, PCIe® 4.0 x4 | 256GB / 512GB / 1TB | Opal 2.0 |

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Dolby Atmos®

Microphone

Dual-microphone array, 360° far-field, Elevoc Voice

Camera**

- Front HD 720p, with privacy shutter, fixed focus; rear World Facing 5.0-megapixel, autofocus
- Front HD 720p, with privacy shutter, fixed focus
- Front 5.0MP + IR discrete, with privacy shutter, fixed focus, temporal noise reduction
- Front 5.0MP + IR discrete, with privacy shutter, fixed focus, temporal noise reduction; rear World Facing 5.0-megapixel, autofocus

Battery

Battery**

- 41Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)^[1]
- 54.7Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)^[2]

Battery Life^[3]

Configuration 1 (max battery life)
MobileMark® 25: up to 12.7 hr with 676 performance score @250nits
JEITA-BAT 3.0 (Video/Idle): up to 11.37 hr / 20.62 hr @200nits
Local video playback: up to 18.5 hr @150nits

Configuration 2
MobileMark® 25: up to 11.99 hr with 647 performance score @250nits
JEITA-BAT 3.0 (Video/Idle): up to 11.21 hr / 18.88 hr @200nits
Local video playback: up to 17.69 hr @150nits

Notes:

[1], [2] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[3] Configuration 1: WUXGA (touch), AMD Ryzen™ 7 PRO 250, 16GB LPDDR5x, Win 11, 54.7Wh battery, best power efficiency power mode
Configuration 2: WUXGA (touch), AMD Ryzen™ 5 PRO 215, 16GB LPDDR5x, Win 11, 54.7Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 25](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.
Actual battery life will vary and depends on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.
The maximum capacity of the battery will decrease with time, ambient temperature and use.
Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter**^[1]

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|-------|-------------------|-------------|--------------------|------------|------------------------------|--------------|----------------|-------------|--------------|-------------------------|---|
| 13.3" | WUXGA (1920x1200) | Multi-touch | IPS ^[1] | 400nits | Anti-reflection, anti-smudge | 16:10 | 1500:1 | 100% sRGB | 60Hz | 89° / 89° / 89° / 89° | Eyesafe® Certified 2.0, Corning® Gorilla® Glass |

Touchscreen

OGM (One Glass Metal mesh) multi-touch, supports 10-point touch

Screen-to-Body Ratio

83.3%

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

Pen

- Lenovo® Integrated Pen, with built-in rechargeable battery, 4096 levels of pressure sensitivity, on-board garaged and rechargeable
- No pen (with a pen garage ready, purchase separately)

Keyboard

6-row, spill-resistant, multimedia Fn keys, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™**

- Models without NFC:
TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu
Mylar® surface multi-touch 3-button Trackpad, 60 x 115 mm (2.36 x 4.53 inches)
- Models with NFC:
TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu
Glass-like Mylar® surface multi-touch 3-button Trackpad, 60 x 115 mm (2.36 x 4.53 inches)

Mechanical

Dimensions (WxDxH)^[1]

299.0 x 215.0 x 12.0/15.7 (front/rear), 18.35 (maximum) mm;
11.77 x 8.46 x 0.47/0.62 (front/rear), 0.72 (maximum) inches

Weight^[2]

Starting at 1.30 kg (2.87 lbs)

Case Color

Grey

Case Material

Aluminium (top), PC + 40% GF (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth^[1]

MediaTek Wi-Fi® 7 MT7925, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4^[2]

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- Quectel EM061K-GL, 4G LTE CAT6, M.2 card, with embedded eSIM functionality
- No support

SIM Card

- KDDI eSIM Program (Japan)^[3]

- No physical SIM card inbox

Ethernet

No onboard Ethernet^[4]

NFC

- Near Field Communication
- No support

Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi® 7 operation is subject to the regulation rules in each country.

[3] KDDI eSIM Program has no physical SIM card inbox and is for special bid only.

[4] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.

Ports^[1]**Standard Ports**

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 2x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 1.4
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports^{*}**

- 1x Nano-SIM card slot (WWAN support models)
- 1x Smart card reader

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking**Docking**

Various docking solutions supported via Thunderbolt™ or USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® L13 2-in-1 Gen 6 \(AMD\)](#)

SECURITY & PRIVACY**Security****Security Chip**

Discrete TPM 2.0 (TCG certified, FIPS 140-3 certified) and Microsoft® Pluton TPM 2.0, one enabled at one time

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

BIOS Security

- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- Self-healing BIOS

- More BIOS security features, please visit [BIOS Simulator](#)

Other Security

- Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)
- ThinkShield
- Privacy Guard with Privacy Alert (software solution)

MANAGEABILITY

System Management

System Management

DASH

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® L13 2-in-1 Gen 6 \(AMD\)](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping packaging: -20°C (-4°F) to 60°C (140°F)
- Storage without packaging: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

50% recycled aluminium on top cover
50% PCC recycled on aluminium top cover top frame
30% PCC recycled on bottom cover
85% PCC recycled plastic used in key caps
90% PCC recycled plastic used in speaker enclosure
45% PCC recycled plastic + 5% OBP on dummy SMC and dummy SIM cover
25% OBP recycled on fan housing
12% recycled rare earth fan magnet
30% recycled rare earth speaker magnet
90% PCC recycled plastic used in slim GaN 65W adapters and standard 65W adapters
90% PCC recycled plastic used in the battery pack enclosure
90% recycled and/or sustainable content for packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

Eyesafe® Certified 2.0

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

