

Spectralink 7722 and 7742

The Ultimate Wireless Solution for Healthcare Personnel



BENEFITS

- Certified and tested with market leading Call Control and UC (IP-PBX) platforms
- Resistance to disinfectants and easy clean keypad membrane reduces the risk of spreading bacteria and diseases
- Tear-off pull-cord string and alarm button increases security for personnel in high risk environments
- Automatic alarms (if man down, no movement or running is detected) further increases personal safety

The Spectralink 7722 and 7742 wireless DECT handsets combine the high demands for hygiene with enhanced responsiveness and personal safety, and are especially designed for environments where mobility and communication are critical factors for saving lives. The intuitive, ruggedized, and disinfectant-resistant wireless DECT handsets are designed to enable healthcare personnel to be mobile while still within quick reach in critical situations. Integrated with third-party applications, like nurse call or equipment monitoring systems, alarm icons and the integrated alarm button ensure immediate reaction in emergency situations.

Special alarm icons for healthcare environments have been developed ensuring that messages and alarms are easy, fast, and intuitive to understand for the healthcare professionals.

These handsets are designed to meet the high demands of hygiene by healthcare personnel and are certified and tested with market leading Call Control and Unified Communications (UC) (IP-PBX) platforms.

Spectralink 7722 Handset

The Spectralink 7722 handset is disinfectant-resistant with a membrane keypad for easy cleaning to minimize and avoid the spread of bacteria and disease. The IP 64 compliant handset is dust proof and protected against splashing water, enabling caretakers to help patients in wet rooms without detaching the handset.

Spectralink 7742 Handset

The Spectralink 7742 handset extends the capabilities of the Spectralink 7722 handset. Personal safety is reinforced with automatic alarms detectors such as man down and running as well as a tear-off pull-cord string alarm. With the expanded safety features, the Spectralink 7742 handset is ideal for personnel within psychiatric wards, emergency departments and other areas where staff's personal safety might be at risk.

FEATURES

SPECTRALINK 7722, 7742

- TFT color display: 65,000 colors, eight lines of text, 128x160 pixels
- Date and time in display*
- · Four-way navigation key
- · Auto key lock
- Alarm key ready for alarm application**
- Speed dial
- · 12 different ringtones and adjustable ring volume
- · Special ring tones for noisy environments
- Adjustable alerting volume (low battery/low coverage/ incoming message)
- · Alerting on silent mode (display flash or short ring)
- · Headset jack
- · Ringtone in headset
- · Speaker on auto-answer
- · Loud speaker/handsfree
- Vibrating alert
- CLIP
- Telephone book with 350 entries
- Call list of incoming/missed/received calls
- Call list saved in non-volatile memory (up to 40 calls)
- Task list saved in non-volatile memory (up to 50 tasks)
- Messaging (180 characters)

SPECIFICATIONS

APPROVALS

- EMC:
- EN 301 489-1
- EN 301 489-6
- Radio: EN 301 406
- EN 301 406
- EN 300 328 (Bluetooth 7742 only)
- Safety: EN 60950-1

Note: For latest approvals and regulatory compliance, please check our website.

SPEECH / STANDBY TIME

- Spectralink 7720:
 - Speech time: up to 23 (27 hours in economy mode)
 - Standby time: up to 118 hours
- Spectralink 7740:
 - Speech time: up to 22 (25 hours in economy mode)
 - Standby time: up to 90 hours
 - Speech/standby time with Bluetooth enabled: up to 11/50

- · Alarm icons and messaging**
- Disinfectant resistant
- Membrane keypad for easy cleaning
- LED**
- Handset Sharing***
- Full Slot DECT radio
- Software Update Over The Air (SUOTA)
- 14 menu languages (UK, FR, DE, ES, IT, NL, CZ, PL, DK, NO, SV, FI, PT, RU)
- · Subscriptions supported: 15

SPECTRALINK 7742 ADDITIONAL FEATURES

- · Bluetooth headset connection
- Tear-off string**
- Man down detector**
- No movement detector**
- Running detector**
- Automatic Alarm Call***

* System dependent feature. See Feature Reference Guide on support pages at support.spectralink.com for details. ** Application dependent feature. *** License required.

SIZE AND WEIGHT

- Size: 148 x 50.4 x 21.6 mm (5.8 x 2.0 x 0.8 in.)
- Weight: 115 g incl. battery (4.0 oz incl. battery)

BATTERY

- Battery: Li-ion battery
- Easily removable battery with option to use in shift-operation environments
- Battery lifetime under proper charge and discharge conditions: Two years or 500 charging cycles

TEMPERATURE

- Operating temperature: -10 55° C (14° F 131° F)
- Charging temperature: 0° 40° C (32° 104° F)

IP RATING

- According to EN60529:
 - IP 64 classified (dust tight and water splash proof)

TESTS

• Drop test: IEC 60068-2-32

About Spectralink

Spectralink delivers secure, cost-effective mobile communication solutions that empower enterprises to streamline operations, increase their revenues and deliver a positive customer experience – each and every time. Since 1990, Spectralink has deployed millions of devices worldwide across the retail, healthcare, hospitality and manufacturing sectors – providing workers with the industry's most efficient, in-building communications.

For more information, visit spectralink.com or call 303.441.7500.



spectralink.com

info@spectralink.com +1 800-775-5330 North America +45 7560 2850 EMEA

* System dependent fea