

Product data sheet

Specifications



APC Parallel Maintenance Bypass Panel, up to 3 units 10-20kVA 400V Wallmount

SBPAR10K20H-WP

Overview

Lead time

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in VA	60000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Provided equipment	Installation guide User manual

Physical

Height	117.4 cm
Width	56 cm
Depth	21.6 cm
Net weight	48 kg
Mounting support	Wall
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50 Hz
-------------------	-------

Conformance

Standards	EN 50091-2 EN/IEC 62040-3 EN/IEC 62040-1-1 VFI-SS-111
-----------	--

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...9144.00 m

Batteries & Runtime

Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	129.8 cm
Package 1 Width	70.4 cm
Package 1 Length	33.5 cm
Package 1 Weight	52.889 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	3
Package 2 Height	115.5 cm
Package 2 Width	74 cm
Package 2 Length	137 cm
Package 2 Weight	158.667 kg

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Recommended replacement(s)