


OVERVIEW



1. Smart card reader *	5. HDMI
2. Nano-SIM card slot *	6. 2x Thunderbolt 4
3. USB-A (USB 5Gbps), Always On	7. Headphone / microphone combo jack (3.5mm)
4. Kensington Nano Security Slot	

- Notes:
- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

Intel® Core™ Ultra 5 / 7 Processor (Series 3)

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
Core Ultra 5 325	8 (4 P-core + 4 LP E-core)	8	P-core 2.1GHz / LP E-core 1.6GHz	P-core 4.5GHz / LP E-core 3.4GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 47 TOPS
Core Ultra 5 332	6 (2 P-core + 4 LP E-core)	6	P-core 2.5GHz / LP E-core 1.9GHz	P-core 4.4GHz / LP E-core 3.3GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 18 TOPS	Up to 46 TOPS
Core Ultra 5 335	8 (4 P-core + 4 LP E-core)	8	P-core 2.2GHz / LP E-core 1.6GHz	P-core 4.6GHz / LP E-core 3.4GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 47 TOPS
Core Ultra 5 336H	12 (4 P-core + 4 E-core + 4 LP E-core)	12	P-core 1.9GHz / E-core 1.5GHz / LP E-core 1.5GHz	P-core 4.6GHz / E-core 3.4GHz / LP E-core 3.2GHz	18MB Intel® Smart Cache	Intel® Graphics, up to 37 TOPS	Up to 47 TOPS
Core Ultra 7 355	8 (4 P-core + 4 LP E-core)	8	P-core 2.3GHz / LP E-core 1.7GHz	P-core 4.7GHz / LP E-core 3.5GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 49 TOPS
Core Ultra 7 356H	16 (4 P-core + 8 E-core + 4 LP E-core)	16	P-core 1.9GHz / E-core 1.5GHz / LP E-core 1.5GHz	P-core 4.7GHz / E-core 3.5GHz / LP E-core 3.3GHz	18MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 50 TOPS
Core Ultra 7 365	8 (4 P-core + 4 LP E-core)	8	P-core 2.4GHz / LP E-core 1.8GHz	P-core 4.8GHz / LP E-core 3.6GHz	12MB Intel® Smart Cache	Intel® Graphics, up to 40 TOPS	Up to 49 TOPS

AI (Artificial Intelligence)

AI PC Category

Copilot+ PC^[1]

NPU

Up to 50 TOPS

Notes:

[1] Copilot+ PCs have at least 16GB RAM, 256GB storage, and a NPU that runs 40+ TOPs to run the latest AI tools build-in latest Windows® 11 to accelerate productivity and creativity.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Ubuntu Linux^[1]
- Linux^[2]
- No preload operating system

Notes:

[1], [2] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics

Graphics	Type	Memory	Key Features
----------	------	--------	--------------

Intel® Graphics	Integrated	Shared	DirectX® 12 Ultimate
-----------------	------------	--------	----------------------

Monitor Support

Monitor Support^[1]

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- Thunderbolt™ supports up to 8K@60Hz^[2]

Notes:

- [1] Refresh rates >60hz also supported, however max resolution will be limited.
- [2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will “-1” when 8K resolution displayed.

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type**

- LPDDR5X-7467^[1]
- LPDDR5X-8533

Notes:

- [1] Installed memory is actually LPDDR5X-8533 but runs as LPDDR5X-7467 due to platform limitation.

Storage

Max Storage Support^[1]

One drive, up to 1TB M.2 2280 SSD

Storage Slot^[2]

One M.2 2280 PCIe® 5.0 x4 slot

Storage Type**

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	256GB / 512GB / 1TB	Opal 2.0
M.2 2280 SSD	PCIe® NVMe®, PCIe® 5.0 x4 Performance	512GB / 1TB	Opal 2.0

Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.
- PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);
- PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);
- PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

Removable Storage

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Atmos®

Microphone

Dual-microphone array, 360° far-field, Lenovo® Clear Voice

Camera**

- 5.0MP + IR discrete, with privacy shutter, fixed focus, Computer Vision on Image Signal Processor (ISP), temporal noise reduction^[1]
- 5.0MP, with privacy shutter, fixed focus, temporal noise reduction
- No camera

Notes:

^[1] Computer Vision on ISP is only available on the models with preloaded OS.

Battery

Battery**^[1]

- 41Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter
- 54.7Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Battery Life^[2]

Configuration 1 (max battery life)

MobileMark® 30: up to 15.6 hr with 610 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 17.0 hr / 29.7 hr @200nits

Local video playback: up to 30.1 hr @150nits

Alternate configuration 2

MobileMark® 25: up to 13.8 hr with 1055 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 14.9 hr / 24.7 hr @200nits

Local video playback: up to 24.5 hr @150nits

Notes:

^[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

^[2] Configuration 1 (max battery life): WUXGA (non-touch), Intel® Core™ Ultra 5 332, 16GB LPDDR5X, Win 11, 54.7Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA (touch), Intel® Core™ Ultra 5 335, 16GB LPDDR5X, Win 11, 54.7Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 25](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter**^[1]

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (2-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (3-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

^[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
13.3"	WUXGA (1920x1200)	Multi-touch	IPS ^[1]	400nits	Anti-glare	16:10	1500:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0
13.3"	WUXGA (1920x1200)	Non-touch	IPS ^[2]	400nits	Anti-glare	16:10	1500:1	100% sRGB	60Hz	85° / 85° / 85° / 85°	Eyesafe® Certified 2.0

Touchscreen

- On-cell multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

87.8%

Notes:

[1], [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu
Glass-like Mylar® surface multi-touch 3-button Trackpad, 74.3 x 115 mm (2.93 x 4.53 inches)

Mechanical

Dimensions (WxDxH)^[1]

Models	Dimensions
Models with carbon fiber hybrid top cover	299.3 x 207 x 10.25/13.35 (front/rear), 18.15 (maximum) mm; 11.78 x 8.15 x 0.40/0.53 (front/rear), 0.71 (maximum) inches
Models with CFRP top cover	299.3 x 207 x 9.85/12.95 (front/rear), 17.75 (maximum) mm; 11.78 x 8.15 x 0.39/0.51 (front/rear), 0.70 (maximum) inches

Weight^[2]

Models	Weight
Models with 41Wh battery	Starting at 930 g (2.05 lbs)
Models with 54.7Wh battery	Starting at 964 g (2.13 lbs)

Case Color

Black

Case Material**

- CFRP (top), aluminium (bottom)
- CFRP (top), magnesium (bottom)
- Carbon fiber hybrid (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®**[1]

- Intel® Wi-Fi® 7 BE211, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4 (Bluetooth® 6.0 hardware ready)
- Intel® Wi-Fi® 7 BE211, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4 (Bluetooth® 6.0 hardware ready), Intel® vPro® technology support^[2]

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)^[3]
- Snapdragon® X12 LTE Modem, 4G LTE CAT6, M.2 card, with embedded eSIM functionality
- Rolling Wireless RW350R-GL, 5G Sub-6 GHz, M.2 card, with embedded eSIM functionality
- No support

SIM Card**[4]

- KDDI eSIM Program 3-year (Japan)
- KDDI eSIM Program 3-year with international roaming (Japan)
- KDDI eSIM Program 4-year (Japan)
- KDDI eSIM Program 4-year with international roaming (Japan)
- KDDI eSIM Program 5-year (Japan)
- KDDI eSIM Program 5-year with international roaming (Japan)
- No physical SIM card inbox

Ethernet

No onboard Ethernet^[5]

NFC

- Near Field Communication
- No support

Notes:

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.

[3] Wireless WAN upgradable to 4G is only available in EMEA.

[4] KDDI eSIM Program has no physical SIM card inbox and is for special bid only.

[5] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps), Always On
- 2x Thunderbolt™ 4, with USB PD 15-65W and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x Nano-SIM card slot (WWAN support models)
- 1x Smart card reader

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions supported via Thunderbolt™ / USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® X13 Gen 7 \(Intel®\)](#)

SECURITY & PRIVACY

Security

ThinkShield

ThinkShield is a comprehensive security solution that encompasses hardware, software, and supply chain components. For more details, visit [here](#)

Security Chip

Discrete TPM 2.0, TCG certified

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

BIOS Security

- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Self-healing BIOS
- More BIOS security features, please visit [BIOS Simulator](#)

Other Security

- (Optional) Computer Vision-based Human Presence Detection on Image Signal Processor (ISP)
- Camera privacy shutter (camera models)
- (Optional) IR camera for Windows® Hello (facial recognition)

MANAGEABILITY

System Management

System Management^[1]

- Intel® vPro® Enterprise^[2]
- Non-vPro®

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See [Intel® vPro® Platform](#) for details.

[2] Intel® vPro® offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service

- 3-year (1-yr battery) limited onsite service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories^{***[1]}

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® X13 Gen 7 \(Intel®\)](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

30% PCC recycled plastic on CFRP top cover
48% PCC recycled plastic used in display panel frame
90% recycled magnesium on keyboard frame
55% recycled aluminium on bottom cover
85% PCC recycled plastic used in keycaps
90% PCC recycled plastic used in speaker enclosure
95% PCC recycled plastic used in cable holders
100% recycled cobalt used in the battery
90% PCC recycled plastic used in the battery pack enclosure
90% PCC recycled plastic used in 65W standard and 65W slim GaN adapters
100% plastic free packaging

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 9.0

- EPEAT™ Gold Registered^[3]
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

[3] EPEAT™ is registered where applicable, please visit epeat.net for registration status by country.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

Eyesafe® Certified 2.0

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

