optomaeurope.com

# LH351ST

Compact high brightness Short throw Full HD 4LED projector




- **Bright 3300 ISO lumens for lights on viewing - Full HD 1080p 4LED short throw projector**
- **Compact and short throw lens for easy installation - 360-degree and portrait projection**
- **Optoma Management Suite (OMSC)™ - Remotely manage and control your device with real-time monitoring, and scheduling, helping to reduce downtime, streamline operations, and cut operating costs.**
- **Optoma Smart Control App - Streamlines device management allowing you to command, control and make image corrections all from your mobile device.**




The LH351ST is one of Optoma's most compact and hassle-free Full HD short throw projectors to date. Designed for maintenance-free continuous operation, this 3300 ISO lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor.

Compatible with Optoma Management Suite (OMSC)™ and Optoma's latest Smart Control App, control and manage your devices remotely with ease.

# Specifications

EAN: 5 055387 669635 , Colour: White

| | |
|---|---|
| **Display/image** | |
| **Display technology** | DLP® |
| **Resolution** | 1080p Full HD (1920x1080) |
| **ISO 21118 brightness** | 3,300 |
| **Contrast ratio** | 300,000:1 |
| **Native aspect ratio** | 16:9 |
| **Aspect ratio - compatible** | 4:3,16:9,16:10 |
| **Keystone correction - horizontal** | +/-30° |
| **Keystone correction - vertical** | +/-30° |
| **Displayable colours (millions)** | 1073.4 |
| **Horizontal scan rate** | 15 ~ 135Khz |
| **Vertical scan rate** | 24 ~ 120Hz |
| **Uniformity** | 85% |
| **Screen size** | 0.76m ~ 7.62m (30" ~ 300") diagonal |
| **Lamp info** | |
| **Light source type** | 4 LED |
| **LASER life** | 30,000 hours |
| **Optical** | |
| **Throw ratio** | 0.49:1 |
| **Projection distance (m)** | 0.306m - 3.055m |
| **Zoom type** | Fixed |
| **Focal length (mm)** | 6.9 |
| **Native offset** | 107% |
| **Connectivity** | |
| **Connections** | **Inputs** 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm<br>**Outputs** 1 x Audio 3.5mm, 1 x USB-A power 1.5A<br>**Control** 1 x RS232, 1 x RJ45 |
| **General** | |
| **Noise level (min)** | 29dB |
| **Noise level (max)** | 35dB |
| **PC compatibility** | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| **Security** | Security bar, Kensington Lock, Password protected interface |
| **OSD / display languages** | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| **24/7 operation** | Yes |
| **360° operation** | Yes |
| **Operating conditions** | 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 10000ft. |
| **Speaker count** | 1 |
| **Watts per speaker** | 10W |
| **In the box** | AC power cord<br>Remote control<br>2x AAA Batteries<br>Basic user manual |
| **Power** | |
| **Power supply** | AC 100 ~ 240V, 50 ~ 60Hz |
| **Power consumption (standby)** | <0.5W |
| **Power consumption (min)** | 124W |
| **Power consumption (max)** | 226W |
| **Weight and dimensions** | |
| **Dimensions (W x D x H) mm** | 307 x 228 x 125 |
| **Gross weight** | 5 kg |
| **Net weight** | 3.2 kg |

Copyright © 2026, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners.Errors and omissions excepted, all specifications are subject to change without notice.All images are for representation purposes only and may be simulated. **Optoma Smart Control App compatible with selected 4K projector models with compatibility for Full HD models pending... for more information please contact your local Optoma service point.. Smart Control app available via RJ45.* 05102026070909