

Product datasheet

Specifications



APC Service Bypass Panel- 230V; 32A; MBB; Hardwire input; (4) IEC-320 C19 Output

SBP6KRMI2U

Overview

Lead time

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Number of rack unit	2U
Provided equipment	Installation guide Rack mounting brackets User manual

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	66 cm
Net weight	11.36 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Max line current	32 A
Input current limits	32 A
Load capacity	7680 VA
Power factor	0...1

Output

Max current draw	32 A
Number of power socket outlets	4 IEC 60320 C19

Protection type	Circuit breaker
Efficiency	99 %

Conformance

Product certifications	CSA GOST
------------------------	-------------

Environmental

Ambient air temperature for operation	-20...50 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-40...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.3 cm
Package 1 Width	99.1 cm
Package 1 Length	61 cm
Package 1 Weight	22.72 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years (parts only)
----------	----------------------

Recommended replacement(s)