



ARTICONA is Bechtle's own brand of IT accessories for the modern workplace and stands for quality and reliability in everyday business.

USB-C Triple Display Dock

Article number: 6003834

This product delivers outstanding performance through its robust display expansion capabilities and seamless connectivity, whether in the office or at home. It supports extending content across three monitors at stunning 4K resolution via legacy DP and HDMI ports, significantly enhancing productivity. Additionally, it incorporates Power Delivery (PD) charging technology, providing fast charging of up to 96W for laptops through the integrated USB-C interface. With four USB-A ports and USB-C ports, this docking station serves as a dependable and stylish docking solution, streamlining workflows, simplifying cable management, and meeting the rigorous demands of modern work environments.

Highlights:

- Three legacy DP/HDMI ports extend displays to 4K resolution on three screens
- DP1.4 MST technology ensures seamless content expansion on external monitors from your laptop
- USB-C UFP delivers 96W power to laptop
- Two USB-C DFP ports provide 7.5W charging for peripherals
- Robust extension and fast data transmission with two USB-A 2.0, two USB-A 10G ports and two USB-C 10G ports



Bechtle Logistik & Service GmbH
Bechtle Platz 1 | 74172 Neckarsulm | Germany

Specifications:

Product type	Dock
Upstream	USB C 3.2 Gen 2
Downstream	2× DP 1× HDMI 2× USB-C 3.2 Gen 2, 5V/1,5A 1× USB-A 3.2 Gen 2, 5V/1,5A 1× USB-A 3.2 Gen 2, 5V/0,9A 2× USB-A 2.0, 5V/0,5A 1× Ethernet 10/100/1000Mbps 1× 3,5mm TRRS
Supports number of displays	3
Power mode	Self-Powered
Power Charging	PD 3.0 up to 96W
USB C cable length	1M
Security slot	Kensington
Operating System	Windows / Mac OS / Chrome OS / Linux
Operation temperature	0~40 degree Celsius
Storage temperature	-20~70 degree Celsius
Dimensions	190 x 85 x 27 mm
Included in delivery	Dock / 135W Power supply / USB C to C cable / Stand / Screw / Manual
Networking features	Support PXE Boot / WOL / MAPT



Video Matrix:

Standard	DP1.2 HBR2					
	Inputs (plug in)			Output		
	Video 1	Video 2	Video 3	Video 1	Video 2	Video 3
	HDMI	DP	DP	HDMI	DP	DP
1 Display	HDMI			3840x2160@30Hz		
		DP			3840x2160@30Hz	
			DP			3840x2160@30Hz
2 Display	HDMI	DP		1920x1080@60Hz	1920x1080@60Hz	
	HDMI		DP	1920x1080@60Hz		1920x1080@60Hz
		DP	DP		1920x1080@60Hz	1920x1080@60Hz
3 Display	HDMI	DP	DP	1920x1080@30Hz	1920x1080@30Hz	1920x1080@30Hz
Standard	DP1.4 HBR3					
	Inputs (plug in)			Output		
	Video 1	Video 2	Video 3	Video 1	Video 2	Video 3
	HDMI	DP	DP	HDMI	DP	DP
1 Display	HDMI			3840x2160@60Hz		
		DP			3840x2160@60Hz	
			DP			3840x2160@60Hz
2 Display	HDMI	DP		2560x1440@60Hz	2560x1440@60Hz	
	HDMI		DP	2560x1440@60Hz		2560x1440@60Hz
		DP	DP		2560x1440@60Hz	2560x1440@60Hz
3 Display	HDMI	DP	DP	1920x1080@60Hz	1920x1080@60Hz	1920x1080@60Hz
Standard	DP1.4 HBR3 + DSC					
	Inputs (plug in)			Output		
	Video 1	Video 2	Video 3	Video 1	Video 2	Video 3
	HDMI	DP	DP	HDMI	DP	DP
1 Display	HDMI			3840x2160@120Hz		
		DP			3840x2160@120Hz	
			DP			3840x2160@120Hz
2 Display	HDMI	DP		3840x2160@60Hz	3840x2160@60Hz	
	HDMI		DP	3840x2160@60Hz		3840x2160@60Hz
		DP	DP		3840x2160@60Hz	3840x2160@60Hz
3 Display	HDMI	DP	DP	3840x2160@30Hz	3840x2160@30Hz	3840x2160@30Hz



Bechtle Logistik & Service GmbH
Bechtle Platz 1 | 74172 Neckarsulm | Germany