



# 0.3m Cat.6 S/FTP Network Cable, Grey

Part No.: 47700

# **Description**

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6 S/FTP PIMF
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6 S/FTP network cable with support for bandwidth up to 250MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6 cable for operating frequencies up to 250MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6 cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Blue, Red, Green, Yellow, Black, White, Orange, Purple, Grey.

# **Technical details**

#### Connectors

Connector A: RJ45 MaleConnector B: RJ45 Male

Housing Material: Polycarbonate

• Connector Plating: Nickel

• Pin Construction: Copper Alloy

• Pin Plating: Gold plated

• Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)

#### Cable Construction

• Length: 0.3m (0.98ft)

Colour: GreyType: Cat.6

• Jacket Diameter: 6.2mm (0.24in)

• Jacket Material: PVC

Conductor Material: CopperConductor Gauge: 27AWGShielding: Aluminium Braid

## **Specifications**

Supported Bandwidth: 250MHz

Nominal Attenuation: 32.8dB/100m @250MHz

• Minimum Band Radius: 74mm (2.91in)

Operating Temperature: -10°C - 60°C (14°F - 140°F)
Storage Temperature: -20°C - 75°C (-4°F - 167°F)

### Miscellaneous

Packaging Type: Polybag

• Warranty (Years): 10

• Certificated: RoHS, REACH, UL, California Proposition 65

## **Purchasing Information**

No.: 47700

• EAN: 4002888477000

### This product is also available in other lengths

• 47700 - 0.3m (0.98ft)

- 47701 0.5m (1.64ft)
- 47702 1m (3.28ft)
- 47703 1.5m (4.92ft)
- 47704 2m (6.56ft)
- 47705 3m (9.84ft)
- 47706 5m (16.44ft)
- 47707 7.5m (24.61ft)
- 47708 10m (32.81ft)
- 47709 15m (49.21ft)
- 47710 20m (65.62ft)
- 47711 30m (98.43ft)

# © LINDY 2020