



## 3m USB 3.2 Type A to C Cable, Anthra Line

No.: 36919

USB Type A Male to C Male

### Description

Professional choice USB 3.2 Gen 2 Type A to C, cable for commercial and high performance AV and IT installations  
SuperSpeed USB 10Gbps - supports data transfer speeds up to 10Gbps (USB 3.2 Gen 2, USB 3.1 Gen 2, USB 3.1)  
Robust TPE housing, gold plated connectors and contacts  
Triple shielded cable, corrosion resistant tinned copper conductors  
2 year warranty

The Anthra Line USB 3.2 Type A to C cables from Lindy's Cable Lines concept are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line USB 3.2 cables are premium connections that feature triple shielded construction with tinned copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

USB bandwidths up to 10Gbps are supported for rapid transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

Anthra Line USB 3.2 Type A to C cables are available in the following lengths: 0.5m, 1m, 1.5m, 2m and 3m.

We have adapted the naming of our USB 3 cables to follow the updated USB specification.

USB 3.0 and USB 3.1 Gen 1 have been renamed to USB 3.2 Gen 1, supporting data transfer up to 5Gbps

USB 3.1 and USB 3.1 Gen 2 are now called USB 3.2 Gen 2, supporting data transfer rates up to 10 Gbps

USB 3.2 Gen 2x2 is a new standard, supporting data transfer rates up to 20 Gbps

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

### Technical details

#### Connectors

Connector A: USB 3.2 Type A Male

Connector B: USB 3.2 Type C Male

Housing Material: TPE

Shielding in head shell: Copper Foil

Connector Plating: Gold

Pin Construction: Copper

Pin Plating: Gold

Dimensions (approx.) WxDxH:

A:16x47x8.8mm [0.63x1.85x0.35in]

B:13x41x7.75 mm [0.51x1.61x0.31in]

#### **Cable Construction**

Length: 3m [9.84ft]

Standard: USB 3.2 Gen 2 (USB 3.1 Gen 2, USB 3.1)

Power Delivery: -

Max. Power: 15W [5V 3A]

Colour: Black

Type: Round

Jacket Diameter: 5.2mm [0.2in]

Jacket Material: TPE

Conductor Material: Tinned Copper

Conductor Gauge Power: 22AWG

Conductor Gauge Data: 28AWG/28AWG

Shielding: Tinned Copper 65%

#### **Specifications**

Supported Bandwidth: 10Gbps

Maximum Resolution: -

Nominal Attenuation: 0.5Mhz-15Ghz\_40dB

Minimum Bend Radius: 26mm [1.02in]

Operating Temperature: 0°C - 40°C [32°F -104°F]

Storage Temperature: -20°C - 60°C [-4°F -140°F]

#### **Miscellaneous**

Packaging Type: Polybag

Warranty (Years): 2

Product Compliance: RoHS, REACH, California Proposition 65 & UL

#### **Purchasing Information**

No.: 36919

EAN: 4002888369190

#### **This product is also available in other lengths**

36910 - 0.5m [1.64ft]

36911 - 1m [3.28ft]

36912 - 1.5m [4.92ft]

36913 - 2m [6.56ft]

36919 - 3m [9.84ft]