

USB 3.2 Gen 1 Hub & Gigabit Ethernet Converter

Part No.: 43379



Description

- Connects a USB 3.2 Type C or Type A computer to a Gigabit Ethernet network
- Provides three USB 3.2/3.1 Gen 1 / USB 3.0 Type A ports
- USB 3.2/3.1 Gen 1 / USB 3.0 SuperSpeed data transfer rates up to 5Gbps
- Supports 10/100/1000BASE-T, full and half duplex mode
- 2 year warranty

The Lindy USB 3.2 Hub & Gigabit Ethernet Converter allows users to conveniently connect a laptop, ultrabook or tablet to a Gigabit Ethernet network via a Type C or Type A USB port and also provides three additional USB Type A ports.

This converter is ideal for ultrabooks or tablets which do not feature wired network connectivity and may only offer a limited number of USB ports. It features a USB Type A as well as a USB Type C plug for connection to the host computer to cover a wide range of devices.

With its small size and lightweight design this USB 3.2 Hub & Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- Interface: USB Type A and Type C to RJ45 & 3x USB Type A
- Interface Standard: USB 3.2/3.1 Gen 1 / USB 3.0, Gigabit LAN
- Supported Bandwidth: 5Gbps, 10/100/1000Mbps
- Chipset: RTL8153B (LAN), GL3510 (Hub)
- Compatibility: USB Type A and Type C equipped computers (incl. Thunderbolt 3/4)
- Power Delivery: -
- Special Features: Supports Wake on LAN (WoL)

Connectors

- Inputs: 1 x USB Type C and Type A (Male)
- Outputs: 1 x RJ45 (Female), 3 x USB Type A (Female)
- Power: Bus-powered

Physical Properties

- Dimensions WxDxH: 107x28x12.5mm (4.2x1.1x0.49in)
- (Fixed) Cable Length: 150mm (5.91in)
- Housing Material: ABS and Aluminium
- Net Weight: 0.05kg (0.11lb)
- Operating Temperature: 0°C - 40°C (32°F -104°F)
- Storage Temperature: -20°C -605°C (-44°F - 140°F)
- Humidity: 5 - 90% RH (non-condensing)
- Power Requirements: -
- Colour: Grey

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 160x90x21mm (6.3x3.54x0.83in)
- Gross Weight: 0.1kg (0.22lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, CP65

Package Contents

- USB 3.2 Hub & Ethernet Converter
- LINDY Manual

Purchasing information

- No.: 43379
- EAN: 4002888433792

© LINDY 2023