

# Product datasheet

Specifications



## APC NetShelter Rack PDU Advanced, Switched, 3PH, 22.1kW 400V 32A or 17.3kW 415V 30A, 48 Outlets, IEC309

APDU10350SW

### Overview

Lead time

### Main

<b>Main Input Voltage</b>	415 V 3 phases 400 V 3 phases
<b>Product or component type</b>	PDU
<b>PDU type</b>	Switched
<b>Main Output Voltage</b>	240 V
<b>Input Connection Type</b>	IEC 60309 30 A 3P + N + PE
<b>Number of rack unit</b>	0U
<b>Cable length</b>	1.8 m
<b>Communication port protocol</b>	1000BASE-T 10/100BASE-T

### Physical

<b>Colour</b>	Black
<b>Height</b>	178.0 cm
<b>Width</b>	5.6 cm
<b>Depth</b>	7.5 cm
<b>Net weight</b>	9.6 kg
<b>Mounting location</b>	Side
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted
<b>Mounting position</b>	Vertical

### Input

<b>[In] rated current</b>	24 A
<b>Permissible voltage</b>	200...240 V 346...415 V
<b>Input current limits</b>	30 A
<b>Load capacity</b>	17300 VA

---

Network frequency	50/60 Hz
-------------------	----------

## Output

---

Number of power socket outlets	24 C13/C15/C19/C21 24C13/C15
--------------------------------	---------------------------------

## Conformance

---

Product certifications	UKCA TAA compliance
------------------------	------------------------

---

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B CE EN 62368-1
-----------	---

---

IP degree of protection	IP44
-------------------------	------

## Environmental

---

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

---

Relative humidity	5...95 %
-------------------	----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Ambient air temperature for storage	-25...65 °C
-------------------------------------	-------------

---

Storage Relative Humidity	5...95 %
---------------------------	----------

---

Storage altitude	0.00...15240.00 m
------------------	-------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	198 cm
------------------	--------

---

Package 1 Width	13.2 cm
-----------------	---------

---

Package 1 Length	26.2 cm
------------------	---------

---

Package 1 Weight	12.6 kg
------------------	---------

## Offer Sustainability

---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

---

REACH free of SVHC	Yes
--------------------	-----

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--

---

Mercury free	Yes
--------------	-----

---

China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

---

RoHS exemption information	<a href="#">Yes</a>
----------------------------	---------------------

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

## Contractual warranty

---

Warranty	3 years repair or replace
----------	---------------------------

## Recommended replacement(s)