



Vertiv™ VRC Split Rack Cooling System

Flexible Cooling for
Small Rooms and
Edge Applications

**2020 AHR Expo Innovation
Award Finalist**



Vertiv™ VRC Split Rack Cooling System

Vertiv™ VRC Split Rack Cooling

Flexible, Efficient Cooling for Any Small Space

The Vertiv™ VRC split rack cooling system brings flexibility and efficiency to small-space cooling. It is ideal for protecting critical IT equipment in server rooms, network closets, and edge computing spaces where rejecting heat into the building isn't an option. Providing up to 3,500 watts of IT server cooling in a space-saving design, the system includes an outdoor unit that rejects heat into the ambient air, allowing it to operate efficiently regardless of building architecture. The energy-efficient features and scalable capacity of the Vertiv VRC system solve a variety of cooling issues even in your most challenging small spaces.

As growth at the edge of networks continues to expand exponentially, and seek to maximize useful, revenue-generating space in their facilities, room for IT is shrinking. IT managers struggle with how to properly protect critical equipment without sacrificing valuable floor space, especially in areas that lack a double ceiling or a building air conditioning system. Until now, available cooling solutions either lacked the capacity, were too large, or didn't work with the building architecture. The Vertiv VRC split rack cooling system solves that problem with a space-saving solution that can work in any building, including spaces with unconditioned air.

Designed for Any of Your Small Spaces

The Vertiv VRC split rack cooling system is designed specifically for installation in small server rooms, network closets, and edge computing spaces that lack a double ceiling, building air conditioning, or the ability to handle in-building heat rejection. The split system consists of indoor and outdoor units connected with two field-installed copper pipes. The heat removed from IT equipment is transferred through the pipes and rejected outdoors into the ambient air. The indoor unit fits into most standard racks. It can be installed at the top or bottom of the rack, occupying only 6U and freeing up valuable floor and rack space. This configuration makes the Vertiv VRC system a seamless small room cooler, especially those small IT spaces.

Reliable, Efficient Operation Protects Your Equipment and Budget

The Vertiv VRC split rack cooling system provides up to 3,500 watts of IT cooling to critical equipment. Its variable-speed components ensure high efficiency and scalable capacity, delivering only as much cooling as needed for the conditions in the room. This load matching helps reduce energy consumption while reliably meeting your changing IT needs.

Keeping You on Top of Rack Mount Cooling Performance

IT managers can monitor the status of the Vertiv VRC split cooling system on the unit's display or remotely using the plug-in SNMP communication card or Modbus RTU. If cooling ever falls outside of predefined thresholds, staff will receive instant notifications and can take action to protect valuable IT equipment.



Vertiv™ VRC Applications Examples

Vertiv VRC Applications

- Vertiv™ VRC can be installed on 2 post or 4 post racks
- Optional 2 post rack installation kit is available to enable easy installation into 2 post
- It can be installed in both - Open or closed racks



4 Post Rack Installation



2 Post Rack Installation



4 Post Rack Installation in a thermally separated rack

TARGET APPLICATIONS:



Network Closets



Small Server Rooms



Edge Spaces

END USER SEGMENTS:



Retail



Education



Healthcare



Finance



Telecom




Industry

Vertiv™ VRC Split Rack Cooling System

Key Benefits

- Reliably and efficiently satisfies cooling requirements for small room and edge applications up to 3.5 kW per cabinet, regardless of building architecture and independent of a building cooling system
- Requires only 6U due to space-saving form factor that leaves the valuable floor and rack space free in small IT rooms
- Lowers energy consumption and reduces operating costs due to real-time cooling and capacity adjustments
- Offers installation flexibility with options for mounting at the top or bottom of standard racks
- Provides peace of mind and simplified management with unit-level or remote monitoring capabilities
- 2 years standard warranty



Airflow Diagram Vertiv™ VRC

Vertiv™ VRC Split Rack Cooling System Features

- **Rack-mounted indoor unit** requiring only 6U and designed to fit at either the top or bottom of most standard Electronic Industries Alliance (EIA) 19-inch network racks
- **Outdoor unit with compressor** for heat rejection into the ambient air
- **Low ambient air temperature operation** that is down to -15C (5F) on the standard outdoor unit or -34C (-30F) on the low-ambient unit enabling IT equipment cooling during winter months
- **Variable speed compressor and fans** to match cooling with the load in the room
- **Add-on condensate pump** to help remove water and simplify condensate management
- **Multiple monitoring options** include an on-unit display, plug-in SNMP card for monitoring remotely over the network, and Modbus RTU for connection to the building management system
- **Alarm notifications** sent via email or SMS
- **Up to 30m (98ft) piping length** between indoor and outdoor unit
- **Vertical distance between indoor and outdoor unit** from -5m to +15m (from -16.4ft to +49ft)



Standard outdoor unit



Low ambient outdoor unit

Vertiv™ VRC Split Rack Cooling System

Included in the Packaging

| Image | Description: |
|---|---|
|  | <p>L-shape Mounting Rail Kit</p> <ul style="list-style-type: none">• Enable Vertiv™ VRC unit installation into a 19" 4 post Rack |
|  | <p>SIC Card Kit</p> <ul style="list-style-type: none">• Remote monitoring card with housing• SNMP, Web and Modbus protocols |
|  | <p>Condensate Pump Kit</p> <ul style="list-style-type: none">• Automatically removes condensed water from the cooling unit.• 25 ft (7,5m) long drain pipe included in the packaging |
|  | <p>Remote Display</p> <ul style="list-style-type: none">• Change Setpoints and See alarms through user friendly interface• With magnetic holder can be attached to any metal surface• Cable included |

Technical Specifications

| SKU# | VRC202KIT-N | VRC202KIT-L |
|---|--------------------------------------|--------------------------------------|
| Indoor unit model Outdoor unit model | VRC202KIT VRC302KIT | VRC202KIT VRC352KIT |
| Minimum Outdoor Operating Temperature | -15°C (+5°F) | -34°C (-29°F) |
| Region | Europe, Middle East and Africa | Europe, Middle East and Africa |
| Input Voltage | 230V/1Ph/50-60Hz | 230V/1Ph/50-60Hz |
| Net Sensible Cooling Capacity* | 3800W (13000BTU/h) | 3400W (11600BTU/h) |
| Capacity Modulation | 25 - 100% | 25 - 100% |
| Power connection | Hard Wired (terminal block) | Hard Wired (terminal block) |
| Total Current (indoor / outdoor) | 1,5A / 7,2A | 1,5A / 7,2A |
| Refrigerant | R410A | R410A |
| Communications | SNMP, Modbus RTU | SNMP, Modbus RTU |
| Approvals | CE | CE |
| Standard Warranty | 2 years | 2 years |
| Occupied U space | 6U | 6U |
| Dimensions Indoor (H x D x W) | 264 x 602 x 442 mm | 264 x 602 x 442 mm |
| Dimensions Outdoor (H x D x W) | 527 x 282 x 786mm | 527 x 282 x 1158mm |
| Weight (indoor / outdoor) | 23kg/44kg | 23kg/68kg |

*Air Temperature to IT equipment 21°C (70°F), Outdoor air temperature 35°C (95°F)

Optional Accessories

| Accessory | Description | Height |
|--------------------------|---------------|--|
| 2 Post Rack Mounting Kit | 2POSTRMKITVRC | This Kit enables Installation of the Vertiv™ VRC unit in a 2-post rack |

Services

| Service Offering | Description | Included |
|-------------------------------|---|--|
| Preferred Warranty | Two-year protection program for Vertiv™ VRC. It can be purchased only at the point of sale, it is valid throughout the two-year warranty period | Coverage of faulty parts as per standard warranty terms <ul style="list-style-type: none"> Labor and travel coverage as per standard warranty terms 8 working hours response time One annual preventive maintenance visit 24x7 access to professional helpline |
| Integrated Warranty Extension | One-year after-warranty protection program | Coverage of faulty parts excluding consumables <ul style="list-style-type: none"> Labor and travel coverage 8 working hours response time One annual preventive maintenance visit 24x7 access to professional helpline |
| Additional Services | Additional services available on 8x5 or 24x7 basis | <ul style="list-style-type: none"> Electrical and mechanical installation Start-up |



Vertiv.com | Vertiv Headquarters, 1050 Dearborn Drive, Columbus, OH, 43085, USA

© 2020 Vertiv Group Corp. All rights reserved. Vertiv™ and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

SL-70542 (R06/20)