

# 482.6 mm (19") installation system

## Imperial installation

### Blanking panel, 482.6 mm (19")

As an extension cover or for population as required.

**Width:**

- 482.6 mm

**Material:**

- Sheet steel

**Colour RAL 7035**

Units U	Installation height mm	Width	Packs of	Model No.
1	44	19"	2 pc(s).	<b>7151.035</b>
1.5	66	19"	2 pc(s).	<b>7157.035</b>
2	88	19"	2 pc(s).	<b>7152.035</b>
3	132.5	19"	2 pc(s).	<b>7153.035</b>
6	266	19"	2 pc(s).	<b>7156.035</b>

**Colour RAL 9005**

Units U	Installation height mm	Width	Packs of	Model No.
1	44	19"	2 pc(s).	<b>7151.005</b>
2	88	19"	2 pc(s).	<b>7152.005</b>
3	132.5	19"	2 pc(s).	<b>7153.005</b>
6	266	19"	2 pc(s).	<b>7156.005</b>



### Blanking panel, 482.6 mm (19")

**Tool-free attachment**

The blanking panel is used to seal unused areas within the 482.6 mm (19") mounting level. Quick tool-free attachment means that it is easily integrated anywhere, and can also be removed again if necessary. The consistent use of blanking panels ensures targeted air routing in partially populated racks.

**Material:**

- Plastic
- Fire protection: Self-extinguishing, to UL 94 HB, halogen-free

**Colour:**

- RAL 9005

**Supply includes:**

- Blanking panel, 1 U, with integral quick-fastening

Installation height U	Width	Packs of	Model No.
1	19"	10 pc(s).	<b>5302.200</b>



### Vent trim panel, 482.6 mm (19")

For targeted air infeed from the front zone into the 482.6 mm (19") level.

**Applications:**

- Targeted routing of cold air from the raised floor via the front to the rear for cooling separate components

**Benefits:**

- Vented surface area approx. 85 % perforated

**Material:**

- Sheet steel

**Surface finish:**

- Spray-finished

**Colour:**

- RAL 9005



**Also required:**

- 482.6 mm (19") fastener, 1 U, see page 1097
- Multi-tooth screws, see page 1098

